

Multilingual Version

[English](#)

[中文](#)

NETWORK CAMERA SERIES

OPERATION GUIDE

Please read instructions thoroughly before operation and retain it for future reference.

IMPORTANT SAFEGUARD



All lead-free products offered by the company comply with the requirements of the European law on the Restriction of Hazardous Substances (RoHS) directive, which means our manufacture processes and products are strictly "lead-free" and without the hazardous substances cited in the directive.



The crossed-out wheeled bin mark symbolizes that within the European Union the product must be collected separately at the product end-of-life. This applies to your product and any peripherals marked with this symbol. Do not dispose of these products as unsorted municipal waste. Contact your local dealer for procedures for recycling this equipment.



This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Federal Communications Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device must not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

Trademark Acknowledgements

iPad® & iPhone® are the registered trademarks of Apple Inc.

Android™ is a trademark of Google Inc. Use of this trademark is subject to Google Permissions.

Microsoft®, Windows® & Internet Explorer® are registered trademarks of Microsoft Corporation in the United States and/or other countries.

Disclaimer

We reserve the right to revise or remove any content in this manual at any time. We do not warrant or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of this manual. The content of this manual is subject to change without notice.

This product doesn't have a standby / off mode.

MPEG4 Licensing

THIS PRODUCT IS LICENSED UNDER THE MPEG4 VISUAL PATENT PORTFOLIO LICENSE FOR THE PERSONAL AND NON-COMMERCIAL USE OF A CONSUMER FOR (i) ENCODING VIDEO IN COMPLIANCE WITH THE MPEG4 VISUAL STANDARD ("MPEG-4 VIDEO") AND/OR (ii) DECODING MPEG4 VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL AND NON-COMMERCIAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED BY MPEG LA TO PROVIDE MPEG4 VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION INCLUDING THAT RELATING TO PROMOTIONAL INTERNAL AND COMMERCIAL USES AND LICENSING MAY BE OBTAINED FROM MPEG LA, LLC. SEE [HTTP://WWW.MPEGLA.COM](http://WWW.MPEGLA.COM).

GPL Licensing



This product contains codes which are developed by Third-Party-Companies and which are subject to the GNU General Public License ("GPL") or the GNU Lesser Public License ("LGPL").

The GPL Code used in this product is released without warranty and is subject to the copyright of the corresponding author.

Further source codes which are subject to the GPL-licenses are available upon request.

We are pleased to provide our modifications to the Linux Kernel, as well as a few new commands, and some tools to get you into the code. The codes are provided on the FTP site, and please download them from the following site or you can refer to your distributor:

http://download.dvrtw.com.tw/GPL/076D_Series/arm-linux-2.6.tar.gz

TABLE OF CONTENTS

1. OVERVIEW.....	1
1.1 Product Features	1
1.2 Package Content	1
1.3 Cable Overview	1
2. CAMERA ACCESS WITH INTERNET EXPLORER.....	2
2.1 Camera Login	2
2.2 Control Panel Overview	2
2.3 Digital PTZ (DPTZ) Operations	4
2.4 Event Record Search & Playback	5
3. CAMERA CONFIGURATIONS.....	6
3.1 System configuration menu	6
3.2 Network	7
3.2.1 Network	7
3.2.2 QoS	7
3.2.3 DDNS	7
3.2.4 SNTP	8
3.2.5 FTP.....	8
3.2.6 MAIL	8
3.2.7 SMS.....	9
3.2.8 Filter	10
3.2.9 UPnP / Bonjour.....	10
3.2.10 RTP	11
3.3 Camera.....	12
3.3.1 Camera.....	12
3.3.2 Video	12
3.3.3 Color.....	13
3.3.4 Advance.....	13
3.4 Record.....	14
3.4.1 Record.....	14
3.4.2 Record Timer.....	14
3.5 Storage.....	14
3.5.1 Memory	14
3.6 Trigger	15
3.6.1 Trigger	15
3.7 General.....	16
3.7.1 General.....	16
3.7.2 Time.....	16
3.7.3 Server Log.....	17
3.7.4 Online	17
3.7.5 Account.....	18
3.7.6 Google Maps	18
3.7.7 Maintenance.....	19
APPENDIX 1 PRODUCT SPECIFICATIONS.....	21
APPENDIX 2 BIT RATE TABLE FOR REFERENCE	22
APPENDIX 3 POE CONNECTION	24
APPENDIX 4 API ID APPLICATION FOR SMS MESSAGING.....	25
APPENDIX 5 Q&A	27
APPENDIX 6 RECORDING TIME TABLE	28

1. OVERVIEW


1.1 Product Features

- Easy **network setup** with your **iPhone / iPad**
- **ONVIF** standard supported to simplify system integration
- **POE (Power-over-Ethernet)** support to eliminate the use of power cables and reduce installation costs
- **External alarm I/O device** connection
- **Remote Surveillance**
 - **Fully compatibility** on **iPhone & iPad**, and **Internet Explorer®** on Windows® operating system
- 35 IR LEDs built-in for **night surveillance**
- **1.3 Megapixel** with **HDTV 720p** quality, allowing users to notice minor details more easily


1.2 Package Content

<input type="checkbox"/> Network camera	<input type="checkbox"/> Bracket	<input type="checkbox"/> Quick Setup with iPhone / iPad
---	----------------------------------	---

1.3 Cable Overview



Color	Cable	Description
--	Power cable	Connect to DC12V power supply. Note: The power adapter is optional.
--	RJ45 network cable	Connect it to the supplied RJ45 cable extender adapter for cable extension, and prepare another RJ45 network cable with suitable length for your connection.
Black & Brown	GND	Ground wire, used for reset default or external device connection.
Yellow	Alarm-in	Reserved for connecting to an external alarm device. For details, please refer the user manual of your alarm device.
Pink	Alarm-out	Reserved for connecting to an external alarm device. For details, please refer the user manual of your alarm device.
Red	RESET	Remove the insulating coating of this wire, and twist it with a ground wire together to reset default. This will reset all parameters, including the IP address to factory default settings. Note: Disconnect power before twisting these two wires together, and connect to power again for reset default.



2. CAMERA ACCESS WITH INTERNET EXPLORER

This network camera can be accessed via Microsoft® Internet Explorer® and iPhone / iPad / Android mobile devices with our self-developed program “EagleEyes” installed depending on different using situations.

Note: For details about accessing network cameras via iPhone / iPad / Android mobile devices, please refer to <http://www.eagleeyesccctv.com>.

Before using the camera, make sure you have configured the network settings, and the network connection is fine.

For network configurations, please refer to:

- **“Quick Setup With iPhone / iPad”** supplied with your camera if you’re using iPhone / iPad, and your network environment is wireless.
- **“ADVANCED NETWORK SETUP”** downloadable from www.surveillance-download.com/user/m357a.swf if your network environment is not wireless.

2.1 Camera Login

Step1: Open your web browser, and key in <http://ipaddress:portnum> in the URL address box.

For example, for the IP address 60.121.46.236 and port No. 888, please key in “<http://60.121.46.236:888>” into the URL address box, and press “Enter”.

Step2: In the login page, key in the user name and password, and enter the security code from the image below if any. Then, click “LOGIN”.

Step3: The wizard is then started.


- To skip the wizard and directly access the camera live view, click “Close”.
- To directly access the camera live view without starting the wizard for the login next time, check “Do not start wizard at login”.












Note: If you’re prompted to install “VLC player”, “Software” and “H264 Streaming Viewer”, please agree to proceed the installation.

Step5: When the login is successful, the live view is shown.

2.2 Control Panel Overview

Note: The buttons available depend on the user level used to log in.




Function	Icon	User Level	Description
Live		Supervisor / Power User / Normal User / Guest	Switch to the live view page.
DPTZ		Supervisor / Power User / Normal User	Switch to the DPTZ configuration page. For details, please refer to “2.3 Digital PTZ (DPTZ) Operations” at page 4.
Backup		Supervisor / Power User	Enter the event record list for video playback. For details, please refer to “2.4 Event Record Search & Playback” at page 4.
Config.		Supervisor / Power User	Switch to the system configuration page, and the functions available for “Supervisor” and “Power User” are different. For details, please refer to “3.1 System configuration menu” at page 6.
Media Type	--	Supervisor / Power User / Normal User / Guest	Select the image player from the drop-down list: <ul style="list-style-type: none"> ■ H.264 / MPEG-4 / Motion JPEG ■ QuickTime <p>QuickTime is Apple Inc.'s multimedia software. You need to have QuickTime installed in your operating system before selecting “QuickTime”. When it is selected, you will be promoted to enter the user name and password to access the camera.</p> <ul style="list-style-type: none"> ■ VLC
Quality	--	Supervisor / Power User / Normal User	Click & drag the slider to select the video quality: BASIC / NORMAL / HIGH / BEST.
Video Resolution	--	Supervisor / Power User / Normal User	Select the image resolution from the drop list: <div> <div>2 megapixel model</div> <div>1.3 megapixel model</div> </div> <ul style="list-style-type: none"> ■ HD1080P (1920 x 1080) ■ HD720P (1280 x 720) ■ VGA (640 x 480) ■ QVGA (320 x 240)
Live View Size:		Supervisor / Power User / Normal User	
Full Screen			Click to display the image in full screen. To exit the full screen mode, press “Esc” on your keyboard. <i>This icon appears only when the selected resolution is HD1080P, SXGA or HD720P & VGA.</i>
Double size			The QVGA resolution is resized to fit into the current live view size. <i>This icon appears only when the selected resolution is QVGA.</i>
Normal Size			The current live view size is the same as the selected resolution. <i>This icon appear only when the selected resolution is SXGA or HD720P or HD1080P.</i>
Fit to screen			The selected resolution is resized to fit into the current live view size. <i>This icon appear only when the selected resolution is SXGA or HD720P or HD1080P.</i>
No Scale			Click and hold the movable square on the left bottom corner of the live view to move <i>This icon appear only when the selected resolution is SXGA or HD720P or HD1080P.</i>
Snapshot		Supervisor / Power User / Normal User	Click to take a snapshot of the current view on a new window. Right click on the picture and re-save it to the location you want.
Alarm Out		Supervisor / Power User / Normal User	Click to force your alarm-out device to work. For example, when your alarm device is a buzzer, click this button and your buzzer will start to sound even if there's no alarm event.

2.3 Digital PTZ (DPTZ) Operations

This camera has PTZ capability, i.e. digital PTZ (hereafter called “DPTZ”), for wide area monitoring.

STEP1: Click “DPTZ” to show the DPTZ control panel.



STEP2: Select the functions when needed:

FUNCTION	ICON	DESCRIPTION
Resolution	--	Select the video resolution for the DPTZ function. Only “VGA” and “QVGA” are available.
Take snapshots		Click to take a snapshot of the current view on a new window. Right click on the picture and re-save it to the location you want.
Alarm Out		Click to force your alarm-out device to work. For example, when your alarm device is a buzzer, click this button and your buzzer will start to sound even if there’s no alarm event.

2.4 Event Record Search & Playback

This camera can only save up to three alarm recordings.

Note: To save more recorded data, it's recommended to use this camera with the compatible NVR.

Time Search

Mode: Time

Start: 2011/03/28
21 : 26 : 37

Stop: 2011/03/28
22 : 26 : 37

Download

Calendar Search

Mode: Calendar

2011
Jan Feb Mar Apr May Jun
Jul Aug Sep Oct Nov Dec
March
Sun Mon Tue Wed Thu Fri Sat
1 2 3 4 5
6 7 8 9 10 11 12
13 14 15 16 17 18 19
20 21 22 23 24 25 26
27 28 29 30 31
Select Time: 00:00 - 00:00
Start

IP CAMERA

Wizard | Live | DPTZ | Backup | Config. | admin | Logout

Backup

Mode: Full List
Event: EXTERNAL ALARM,...

Start: 2011/08/31
05 : 29 : 00

Time










2011/08/31 05:28:58
2011/08/31 05:28:47
2011/08/31 05:28:35
2011/08/31 05:28:25
2011/08/31 05:28:14
2011/08/31 05:28:03
2011/08/31 05:27:52
2011/08/31 05:27:41
2011/08/31 05:27:31

Reload Prev Next
Start

00:00 01:00

Event Icon

External Alarm

	Previous / Next Hour	Click to jump to the next / previous time interval in an hour, for example, 11:00 ~ 12:00 or 14:00 ~ 15:00, and start playing the earliest event video clip recorded during this whole hour.
	Fast Forward	Increase the speed for fast forward. Click to get 2X, 4X, 8X & 16X speed forward eventually.
	Fast Rewind	Increase the speed for fast rewind. Click to get 2X, 4X, 8X & 16X speed rewind eventually.
	Play	Click to play the current video clip.
	Pause	Click to pause the video playback.
	Stop	Click to stop the video playback.
	Step	In the pause mode, click to get one frame forward.
	Audio	Click to mute the playback if necessary, and click again to restore.
	Download	Click to download the current video clip to the specified path in your PC. <i>The downloaded video can only be opened by our own video player. Please go to "General" → "Maintenance" to download the video player, or get the player from the CD supplied with the sales package.</i>

3. CAMERA CONFIGURATIONS

Users can further configure this network camera by accessing via Internet Explorer.

3.1 System configuration menu

Click “Config.” to enter the configuration page.

The functions are categorized into six menus: Network, Camera, Record Timer, Storage, Trigger and General.

- For details about “Network”, please refer to “3.2 Network” at page 7.
- For details about “Camera”, please refer to “3.3 Camera” at page 12.
- For details about “Record”, please refer to “3.4 Record” at page 14.
- For details about “Storage”, please refer to “3.5 Storage” at page 14.
- For details about “Trigger”, please refer to “3.6 Trigger” at page 15.
- For details about “General”, please refer to “3.7 General” at page 16.

Main Menu	Sub-Menu	Reference
Network	Network	Configure network settings.
	QoS	Limit the data flow for live streaming.
	DDNS	Enter DDNS information when the network type is PPPOE or DHCP.
	SNTP	Synchronize your camera time with the networked computer systems.
	FTP	Enter the FTP information for event notifications when “FTP” is chosen in “Trigger” → “Trigger”.
	Mail	Enter Email information for event notifications when “Email” is chosen in “Trigger” → “Trigger”.
	SMS	Enter text messaging information for SMS notifications when “SMS” is chosen in “Trigger” → “Trigger”.
	Filter	Choose to permit or block the IP address(es) which can access this camera.
	UPnP	<i>*Suitable for Windows-based operating system.</i> Allow this camera to be detected among devices within the same network area for easy and quick usage.
	Bonjour	<i>*Suitable for Apple Mac-based operating system.</i> Allow this camera to be detected among devices within the same network area for easy and quick usage.
	RTP	Set the parameters for video data transmission when you’re using multimedia other than web browsers and Video Viewer for remote access.
Camera	Camera	1. Rename the camera. 2. Change the place where the camera name is shown on the screen.
	Video	Adjust video-related settings in different video format.
	Color	Adjust the color performance.
	Advance	Adjust the camera parameters if necessary.
Record	Record	Configure the record function.
	Record Timer	Schedule external alarm recording.
Storage	Memory	Check the current storage capacity and clear all recorded data when needed.
Trigger	Trigger	1. Enable / disable the motion detection. 2. Set the motion detection area. 3. Configure how the camera reacts for any event.

Main Menu	Sub-Menu	Reference
General	General	<ol style="list-style-type: none"> 1. Select the language of the web browser. 2. Check the MAC address of the camera. 3. Lock camera access after the specified time.
	Time	Set daylight saving time and the current time.
	Server Log	Check the system event logs.
	Online	Check the current online user(s).
	Account	<ol style="list-style-type: none"> 1. Create a new user account with different access privilege. 2. Modify or delete an existing user account.
	Google Maps	Allow you to know where the network camera is.
	Maintenance	<ol style="list-style-type: none"> 1. Check the current firmware version and upgrade your camera. 2. Copy system configurations. 3. Reboot the camera. 4. Download the video player to play the recorded data.

3.2 Network

3.2.1 Network

You can set the network configuration of the network camera depending on your network type.

For details, please refer to “Advanced Network Setup” from www.surveillance-download.com/user/m357a.swf.

3.2.2 QoS

QoS, Quality of Service, is the ability to control the data flow for real-time streaming. This function is important if your network bandwidth is insufficient and you have other devices to share the network bandwidth.

Check “QoS Enable”, and set the max. upload rate from 256 to 10240 kbps.

3.2.3 DDNS

Select “On” when the selected network type in “Network” is “PPPOE” or “DHCP”.

For details, please refer to “Advanced Network Setup” from www.surveillance-download.com/user/m357a.swf.

3.2.4 SNTP

SNTP (Simple Network Time Protocol) is used to synchronize your camera time with the networked computer systems.

The SNTP Configuration interface includes the following fields and controls:

- GMT:** A dropdown menu currently set to "(GMT+08:00) Taipei".
- NTP Server:** A text input field containing "tock.stdtime.gov.tw".
- Sync. Period:** A dropdown menu currently set to "Daily".
- Server Time:** A text input field showing "2011-08-30 20:34:42".
- Buttons:** A "Sync." button with a circular arrow icon, and "Save" and "Reload" buttons at the bottom.

Function	Description
GMT	Once users choose the time zone, the network camera will adjust the local area time of the system automatically.
NTP Server	Simply use the default SNTP server (For example, tock.stdtime.gov.tw) or change to another server with which users are familiar.
Sync. Period	Select "Daily" to synchronize the camera time with the network time every day or "None" to turn off this function.
Sync	Click and the network camera will synchronize the time with the network time.

3.2.5 FTP

Enter the detailed FTP information and click "Save" to confirm. The information you set here will be applied when "FTP" is selected in "Trigger" → "Trigger".

The FTP Configuration interface includes the following fields and controls:

- Username:** A text input field containing "manager".
- Password:** A text input field containing "*****".
- Server:** A text input field containing "192.168.2.32".
- Port:** A text input field containing "21".
- Directory:** A text input field containing "upload".
- Buttons:** "Save" and "Reload" buttons at the bottom.

3.2.6 MAIL

Enter the detailed e-mail information and click "Save" to confirm. The information you set here will be applied when "Email" is selected in "Trigger" → "Trigger".

The SMTP Configuration interface includes the following fields and controls:

- SMTP Server:** A text input field containing "smtp.gmail.com".
- Port:** A text input field containing "465".
- Mail From:** A text input field containing "manager".
- SSL Encryption:** Radio buttons for "Yes" (selected) and "No".
- Verify Password:** Radio buttons for "Yes" (selected) and "No".
- Username:** A text input field containing "manager".
- Password:** A text input field containing "*****".
- Buttons:** "Save", "Test" (with a mail icon), and "Reload" buttons.

The E-Mail Address List interface includes the following controls and data:

- Controls:** "Add", "Edit", and "Delete" buttons.
- Table:**

Receiver Name	E-Mail Address
boss	boss@tech.com

Function	Description
SMTP Server	Enter the SMTP server address provided from your e-mail system supplier.
Port	Enter the port number provided from your e-mail system supplier. If this column is left blank, the e-mail server will use port 25 to send e-mails.
Mail From	Enter the name of the sender.
SSL Encryption	Select "Yes" if your e-mail server is using SSL encryption to protect your e-mail content from unauthorized access.

Function	Description
Verify Password	Some mail servers are required to verify the password. Please enter the “user name” and “password”.
E-Mail Address List	Add the e-mail address(s) of the assigned recipient(s).
Test	When all information is entered, click “Test Mail” to try if the receipt.

3.2.7 SMS

Note: Before using this function, you need to apply an API ID from the mobile messaging company, Clickatell, and you will be charged starting from the 11th message. For details, please refer to “APPENDIX 4 API ID APPLICATION FOR SMS MESSAGING” at page 25.

Enter the detailed information needed for text messaging, and click “Save” to confirm. The information you set here will be applied when “SMS” is selected in “General” → “Trigger”.

The screenshot shows the 'SMS Configuration' window. It contains the following fields and controls:

- System:** A dropdown menu with 'clickatell' selected.
- Username:** A text input field containing 'tech'.
- Password:** A text input field with masked characters '*****'.
- API ID:** A text input field containing '3281378'.
- Recipient:** A text input field containing '+886912665475'.
- Transfer Interval:** A dropdown menu with '15' selected, followed by the text 'Minute(s)'.
- Message:** A text area containing '[192.168.1.10] unauthorized access!'.
- Reset Counter:** A button with a circular arrow icon.
- Include Hostname or IP:** A checked checkbox.
- Buttons:** 'Save', 'Test', and 'Reload' buttons at the bottom.

Function	Description
System	The text messaging service provider is Clickatell.
User name / Password	Enter the account user name and password you created in Clickatell.
API ID	Enter the API ID you applied from Clickatell.
Recipient	Click “Add” to enter the phone number, including the country code, to receive the text message. Five sets of phone numbers are allowed.
Transfer Interval	Set the interval time in minutes between two-message sending. The options are 0, 15, 30 & 60.
Reset Counter	Click to restart the text messaging, and the SMS will be sent after the specified time interval since you click this button.
Message	Enter the text content (up to 70 characters) you want to send with the text message.
Test	To know whether your SMS setting is correct, click this button to immediately send a SMS to your phone. Note: This testing is not free and you will be charged for SMS sending base on your local rate.

3.2.8 Filter

Choose to permit or block the IP address(es) which can access this camera, and click “Save” to confirm.

Filter Configuration

Error Count: 3

Error Lock Time: 1 Minute(s)

Echo Request: ☒ Non-Block ☐ Block

IP/MAC Filter Configuration

IP/MAC Filter: ☒ Enable ☐ Disable

IP/MAC Filter Policy: ☒ Allow ☐ Deny

IP/MAC Filter Rules

Rule : 192.168.1.122 + Add - Delete Help

192.168.1.23

Save Reload

Function	Description
■ Filter Configuration	
Error Count	Set the maximum count for login failure. When the maximum count is reached, the IP address trying to access the network camera will be locked.
Error Lock Time	Set the lock time in minutes when the maximum count of error login for an IP address is reached.
Echo Request	Select “Non-Block” to allow other users to use the ping command to detect the IP address of your network camera, or “Block” to deny the ping command request.
■ IP/MAC Filter Configuration	
IP/MAC Filter	Choose to enable or disable the filter function.
IP/MAC Filter Policy	If “Enable” is selected, choose whether you want to permit (Allow) or block (Deny) the IP address list below.
■ IP/MAC Filter Rules	
Rule	<ul style="list-style-type: none">To add an item to the IP address list, key in the IP address in “Rule”, and click “Add”.To remove an existing item in the IP address list, click the item you want to remove, and click “Delete”.

3.2.9 UPnP / Bonjour

“UPnP” stands for “Universal Plug and Play”, which allows devices to connect seamlessly in the home and corporate environments and simplify installation of computer components, and is only suitable for Microsoft Windows-based operating system.

“Bonjour” functions the same as “UPnP”, but it’s only suitable for Apple Mac-based operating system.

➤ UPnP

UPnP Configuration

UPnP: ☒ Enable ☐ Disable

Friendly Name: IP CAMERA (Fixed) 000E531574E3

Save Reload

➤ Bonjour

Bonjour Configuration


Bonjour: ☒ Enable ☐ Disable

Device Name: IP CAMERA (Fixed) AVN806-000E5320E73E

Save Reload

Check “Enable” to allow the network camera to be detected among devices within the same network area, and set the identification name of the camera in “Friendly name”.

When this function is activated, the other PC within the same domain as this camera will be able to search this camera in:

- “Network Neighbor” with the identification name set in “Friendly name” for Windows-based PC, or
- “” (finder) or “Bookmark” with the identification name set in “Device Name” for Mac-based PC.

Double-click it to quickly open the web browser for camera access.


Port Mapping (Available only in UPnP)

This function can eliminate the need to additionally access the router for port forwarding.

For details, please refer to “Advanced Network Setup” from www.surveillance-download.com/user/m357a.swf.

Note: Before using this function, make sure your router supports UPnP, and this function is enabled. If not, please access your router additionally for port forwarding.

When “Port Mapping” is set to “Enable”, the system will automatically assign an IP address or port number for you if no IP address or port number is entered.



The Port Mapping Configuration window shows the following settings:

- Port Mapping: ☒ Enable ☐ Disable
- Your IP-Camera is accessible from the other side of the router using the following URL:
http://60.248.97.4:80 or https://60.248.97.4:59207.
- Router IP: (LAN IP Address)
- HTTP Port: 80
- HTTPS Port: 59207
- *If set to blank or 0, a port number will be set automatically upon enable.
- Buttons: Save, Reload

Note: When the configurations are saved successfully, you’ll see a message indicating the IP address and port number assigned to this network camera.


3.2.10 RTP

The Real-time Transport Protocol (RTP) is an Internet protocol standard to manage the real-time transmission of multimedia, such as VLC player.

The media player you want to use for remote access must support RTP transmission for this function to work normally.

Note: When you’re about to end the remote access, please press the stop button on your media player first, and then close the program. This is to ensure the server receives the stop command, and also help to protect the server from redundant data transmission.

Note: QQVGA is for mobile surveillance only.



The RTP Configuration window shows the following settings:

- Port Range**
 - Start Port: 50000
 - End Port: 60000
- Multicast**
 - H264**

Resolution	Address	Port
SXGA / HD720P	239.101.101.102	9000
VGA	239.101.101.103	9000
QVGA	239.101.101.104	9000
QQVGA	239.101.101.105	9000
 - MPEG4**

Resolution	Address	Port
SXGA / HD720P	239.101.102.102	9000
VGA	239.101.102.103	9000
QVGA	239.101.102.104	9000
QQVGA	239.101.102.105	9000
 - JPEG**

Resolution	Address	Port
SXGA / HD720P	239.101.103.102	9000
VGA	239.101.103.103	9000
QVGA	239.101.103.104	9000
QQVGA	239.101.103.105	9000
- Time to Live (TTL): 15
- Buttons: Save, Reload

Function	Description
■ Port Range The port range used by RTP is limited, and preserving 100 ports between the start port and end port is necessary.	
Start Port	The range of the start port is 1024 ~ 65434.
End Port	The range of the end port is 1124 ~ 65534.
■ Multicast	
Address and port for H264 / MPEG4 / JPEG transmission	Set a specific address and port for multicast of each stream format (H264/ MPEG4/ JPEG). The range of the address is limited between 224.0.0.1 ~ 239.255.255.255. The port for multicast must be an even number.
Time to Live (TTL)	The range of Time to Live of the package is between 1 ~ 255. As soon as Time to Live of the package is 0, it will be dropped.

3.3 Camera

3.3.1 Camera

Rename the camera, and change the place where the camera name is shown on the screen, UP-LEFT / UP-RIGHT / DOWN-LEFT / DOWN-RIGHT.

Camera

Camera Configuration

Title:

Position:

3.3.2 Video

Adjust video-related settings in different video format.

- “Quality” is related to image clearness.
- “FPS” is related to the fluency of the video. The more the FPS, the more fluent the video.
- “Max Bit Rate” is the maximum limitation of data transmission in the selected image format and resolution.

Take 2 megapixel model as an example below. For 1.3 megapixel model, please refer to its actual display.

Note: QQVGA is for mobile surveillance only.

Video Configuration

Configuration

Power Line Frequency: Hz

H264

Resolution	Quality	FPS	Max Bit Rate
HD1080P	HIGH	30	8000
HD720P	HIGH	30	8000
VGA	HIGH	30	3000
QVGA	HIGH	30	3000
QQVGA	HIGH	30	3000

MPEG4

Resolution	Quality	FPS	Max Bit Rate
HD1080P	HIGH	15	8000
HD720P	HIGH	30	8000
VGA	HIGH	30	3000
QVGA	HIGH	30	3000
QQVGA	HIGH	30	3000


JPEG

Resolution	Quality	FPS
HD1080P	HIGH	30
HD720P	HIGH	30
VGA	HIGH	30
QVGA	HIGH	30
QQVGA	HIGH	30

3.3.3 Color


Adjust the color performance from Brightness, Contrast, Hue and Saturation. Click and drag the slider to preview the color change on the right side of this page and adjust the image color.

To restore the default values, click “Back to Default”.



3.3.4 Advanced

Adjust the camera parameters if necessary.



Item	Description
Shutter Speed	Set the shutter speed based on your need. The options are: Up to 1/10 sec, Up to 1/30, Up to 1/15, Up to 1/6, Up to 1 and Up to 2.
Mirror	Select “ON” to rotate the images horizontally based on your installation situation when necessary.
Flip	Select “ON” to rotate the image 180° when necessary.
De-noise	Click and drag the slider to adjust the level from 0 ~ 10 to decrease the noise shown in the dark environment.
IR Control	Select “Auto” to automatically enable IR LEDs at night or in the dark environment, “On” to always enable IR LEDs, or “OFF” to disable this function.
White Balance	Process the current image to retain color balance over a color temperature range. The options are: Auto, Incandescent Light, Cool Light, sun Light, Cloudy & Sun Shade.
Sharpness	Sharpness enhances the clarity of image detail by adjusting the aperture and sharpening the edges in the pictures. Hold and drag the slider to adjust the level of sharpness from 0 ~ 100. The higher the value, the sharper the image.


3.4 Record

3.4.1 Record

In “Record Configuration”, you can:

- Enable or disable the alarm record function. When “Enable” is set to “No”, the alarm record function is disabled even if you enable it in other configuration pages.
- Select if the data should be overwritten when the memory storage is full.
- Select the video resolution for event recording.


Note: The higher resolution you choose, the more accuracy and higher image quality the recording will be, but the faster the memory storage is consumed and become full.



3.4.2 Record Timer

To schedule alarm recording, enable it, and select the day and time for recording.

Note: The timer must be enabled for the record function to work properly.



3.5 Storage


3.5.1 Memory

In “Memory”, you can check the remaining capacity for recording, or clear all recorded data saved if needed.

Note: The recorded data will be removed also when you reset or reboot this camera.

Note: To save more recorded data, it's recommended to use this camera with the compatible NVR.

Note: To know the total recording time per recording resolution, please refer to “APPENDIX 6 RECORDING TIME TABLE” at page 28.



The total capacity for recording may vary depending on different models. Please check the actual display of your model.

3.6 Trigger

3.6.1 Trigger

You can configure how this camera reacts when there's an alarm or motion event.

Detect

External Alarm: OFF

Motion: ON

Duration: 10 Sec.

Detection

Action

E-Mail: ☐ External Alarm ☐ Motion

FTP: ☐ External Alarm ☐ Motion

SMS: ☐ External Alarm ☐ Motion


Alarm Out: ☒ External Alarm ☐ Motion

Record: ☐ External Alarm

Save

Reload

◆ Detect

Item	Description
External Alarm	Enable or disable detection from external alarm-in device, and click the title “External Alarm” (in blue) to set “N.O.” or “N.C.” depending on the configuration of your alarm-in device.
Motion	<div>Enable or disable motion detection.</div> <div><i>Motion detection is not supported when the stream format is Motion JPEG.</i></div> <div>When “Enable” is selected, click “Detection” to enter the motion detection area setting page as follows:</div> <div><div><div><div>Detection Configuration</div><div><div>Sensitivity: Normal</div><div></div><div><div>Save</div><div>Reload</div><div>Back</div></div></div></div></div><div>Sensitivity:</div><div>Set the detection sensitivity from the drop-down list: High, Normal or Low.</div><div>Area Setting:</div><div>Set the motion detection area by selecting the area grids with your mouse. Pink grids represent the area that is not being detected while the transparent grids are the area under detection. You can set multiple areas under detection.</div><div>Click “Clear All” to set the whole area undetected.</div><div>Click “Select All” to set the whole area under detection.</div></div>
Duration	Set the duration time for trigger recording (5 / 10 / 20 / 40 seconds).

◆ Action

Here defines how the camera delivers alerts to you for any event.

Item	Description
E-Mail	Select the event type you want to receive E-mail notifications when it occurs. Then, click the title “E-Mail” (in blue) to configure the media type (H264 / JPEG / MPEG4), file format (AVC / AVI), and record time (1 ~ 5 seconds) for the event video clip. The camera will send the captured video clip to the E-mail address(s) you assigned in “Network” → “Mail” once the selected event type occurs.
FTP	Select the event type you want to receive FTP notifications when it occurs. Then, click the title “FTP” (in blue) to configure the media type (H264 / JPEG / MPEG4), file format (AVC / AVI), and record time (1 ~ 5 seconds) for the event video clip. The camera will upload the captured video clip to the FTP site you assigned in “Network” → “FTP” once the selected event type occurs.
SMS	Select the event type you want to receive a text message when it occurs. The camera will send a text message to the mobile phone number you assigned in “Network” → “SMS” once the selected event type occurs.
Alarm Out	Select the event type you want to trigger the alarm-out device to work when it occurs. Then, click the title “Alarm Out” (in blue) to configure the trigger rule (LOW / HIGH).
Record	Select the event type you want to enable event recording when it occurs.


3.7 General

3.7.1 General

To change the language of UI interface, select from the drop-down list in “Language”.


To lock camera access when it's not used after the specified time, select “5 MIN”, “15 MIN” or “30 MIN” from the drop-down list of “Auto Lock Time”, or select “NEVER” to disable this function.

Note: When the camera access is locked after the specified time, to resume camera access, please enter the password.



3.7.2 Time

Set daylight saving time and the current time, and click “Save” to confirm.



Function	Description
■ Time Configuration	
Date	Set the current date.
Time	Set the current time.
■ Daylight Saving Time Configuration	
Daylight Saving Time	Specify whether to use daylight saving time (Enable / Disable).
	If this function is enabled, set the time period (Start Time / End Time), and adjust the daylight saving time in hours (Adjust Time).

3.7.3 Server Log

To quickly search the system logs you want by event type, click “Prev. Page” or “Next Page” to find the logs you want, or check the event type(s) and click “Reload” to start searching.

To clear all system event logs, click “Clear All”.

Server Log List			
No.	Event	Time	Result
1	Remote Login	2011/08/30 20:54:41	admin
2	Remote Login	2011/08/30 20:29:58	admin
3	Remote Login	2011/08/30 18:22:08	admin
4	SNTP Update	2011/08/30 18:20:06	Failed
5	Remote Login	2011/08/30 18:20:03	admin
6	Power On	2011/08/30 18:19:24	ON
7	Power On	2011/08/30 18:18:46	OFF
8	Remote Login	2011/08/30 18:11:21	admin
9	Remote Login	2011/08/30 18:11:18	admin
10	Remote Login	2011/08/30 18:07:10	admin
11	Remote Login	2011/08/30 18:03:19	admin
12	Remote Login	2011/08/30 18:02:15	admin
13	Remote Login	2011/08/30 18:02:07	admin
14	Remote Login	2011/08/30 18:01:51	admin
15	Remote Login	2011/08/30 17:57:01	admin
16	Remote Login	2011/08/30 17:56:55	admin
17	Remote Login	2011/08/30 17:56:53	admin
18	Remote Login	2011/08/30 17:54:44	admin
19	SNTP Update	2011/08/30 17:50:48	Failed
20	Power On	2011/08/30 17:50:07	ON

Prev. Page Next Page Reload Clean All

3.7.4 Online

You can check the current online user(s) with respective online information. To refresh the list, click “Reload”.

- To allow anonymous login, select “Enable” in “Anonymous Viewer Login”.
- To disable image code verification at login, select “No” in “Login with CAPTCHA Image”.

Online Configuration			
Anonymous Viewer Login: <input type="radio"/> Enable <input checked="" type="radio"/> Disable			
Login with CAPTCHA Image: <input type="radio"/> Yes <input checked="" type="radio"/> No			
Max Online User: <input type="text" value="10"/>			
Username	IP Address	User Level	Media Type
admin	211.75.84.96	SUPERVISOR	H264
admin	60.248.97.4	SUPERVISOR	H264
<div>Reload</div>			
<div>Save Reload</div>			

3.7.5 Account

You can create a new account with different user access privilege, or delete or modify an existing account setting.

How to create a new account

Step1: Click “New”, and fill in the following columns.

The screenshot shows a web interface for managing accounts. At the top, there's a table with columns: Username, User Level, and Life Time. The table contains four rows: 'admin' with 'SUPERVISOR' level and 'INFINITE' life time; 'power' with 'POWER USER' level and '1 HOUR' life time; 'normal' with 'NORMAL USER' level and '1 HOUR' life time; and 'guest' with 'GUEST' level and '1 HOUR' life time. Below the table is a 'New Account Info' dialog box. It has five input fields: 'Username' (filled with 'office'), 'Password' (filled with '*****'), 'Confirm Password' (filled with '*****'), 'User Level' (a dropdown menu showing 'POWER USER'), and 'Life Time' (a dropdown menu showing '1 HOUR'). At the bottom of the dialog are 'Save' and 'Close' buttons. A red arrow points to the 'Add' button (a green plus icon) located at the bottom left of the main interface, below the table.

Column	Description
User Name	Set a user name that will be used for camera access. The user name allows up to 16 alphanumeric characters.
Password	Set the password that will be used for remote login. The password allows up to 16 alphanumeric characters.
Confirm Password	Enter the password again to confirm.
User Level	Set the security level of an account to give the permission to control different functions. There are four user levels: SUPERVISOR, POWER USER, NORMAL USER and GUEST.
Life Time	Select how long this account is allowed to stay online (1 MIN / 5 MIN / 10 MIN / 1 HOUR / 1 DAY / INFINITE)

Step2: Then, click “Save” to save your setting and create a new account.

How to modify or delete an existing account

Step1: Select the account you want to modify or delete.

Step2: To modify the account, click “Edit” to change the settings, and click “Save”.
To remove the account, click “Delete”.

Note: It's not allowed to remove an account when there's only one account in the account list.

3.7.6 Google Maps


This function is used to let you know where the network camera is.

The system will prompt you to apply a Google Maps Key if your access is denied. Please follow the instructions below when you're denied:

Step1: Click “Sign up for a Google Maps key” to enter the application page.

Step2: Check the terms and conditions, and enter the IP address of the network camera. Then, click “Generate API Key”.

Step3: Copy the generated API key, and click “Update Google Maps Key” on the web browser to paste it.




3.7.7 Maintenance


Firmware Upgrade

This function is used when users need to upgrade the camera for function scalability.

Note: Before using this function, make sure you have the correct upgrade files provided by your installer or distributor.

Note: The event videos saved in the camera will be removed after firmware upgrade. Make sure you've copied important events to your PC before firmware upgrade.

Step1: Select “” to browse to where you save the upgrade files, and select them one by one until all files are selected (up to four files).



Step2: Select “Upgrade” to start system upgrading.

Note: You'll be prompted to keep current configurations. It's recommended to keep them, or all configurations will be restored to default values after upgrade.


Note: It takes a few minutes to finish the upgrade process. Do not disconnect the power during firmware upgrade, or the upgrade may be failed. The camera will reboot after the upgrade.

System Configuration Backup

This function is used to copy your system configuration to a “System.bin” file.


You may import the same system configuration to another camera, or restore your system configuration when the camera is reset to default values.

Select “System.bin” in “Firmware Upgrade”, and select “Upgrade” to import the system configuration.




System Reboot

Select “Reboot” to restart your camera if needed.



Player Download

To see the event video clips downloaded to your PC, you need to first install our own video player in your PC. Select “Free Download” to download the video player, and double click the file to install it.



APPENDIX 1 PRODUCT SPECIFICATIONS

	2 Megapixel	1.3 Megapixel
■ Network		
Network Compression	H.264 / MPEG4 / MJPEG	
Multiple Video Streaming (Encode Modes, IPS, Resolution)	3 (H.264, MJPEG, MPEG4)	
LAN Port	YES	
LAN Speed	10/100 Based-T Ethernet	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP,IPv4, Bonjour, UPnP, DNS,UDP,IGMP	
Frame Rate	NTSC:30, PAL:25	
Number of Online Users	10	
Security	(1) Multiple user access levels with password (2) IP address filtering (3) Digest authentication	
Remote Access	(1) Internet Explorer® on Windows® operating system (2) EagleEyes on iPhone, iPad & Android mobile devices	
■ Camera		
Image Sensor	1/2.9" SONY HR. image sensor	1/4" SONY HR image sensor
Video Resolution	HD1080P / HD720P / VGA / QVGA	SXGA / HD720P / VGA / QVGA
Min Illumination	0.1 Lux / F1.5, 0 Lux (IR LED ON)	
S/N Ratio	More than 48dB (AGC off)	
Lens	f3.8mm / F1.5	
Viewing Angle	73.2°(Horizontal) / 47.4°(Vertical) / 85.4°(Diagonal)	53.7°(Horizontal) / 34.1°(Vertical) / 62.7°(Diagonal)
IR LED	35 units	
IR Effective Range	Up to 20 meters	
IR Shift	YES	
White Balance	ATW	
AGC	Auto	
IRIS Mode	AES	
POE	YES (IEEE 802.3af)	
External Alarm I/O	YES	
IP Rating	IP67	
Power Source (±10%)	12V / 1A	
Operating Temperature	-20℃~40℃	
Dimensions (mm)**	75(φ) x 114(H)	
■ Others		
Mobile Surveillance	iPad, iPhone & Android mobile device	
RTC (real-time clock)	YES	
Motion Detection	YES	
Event Notification	FTP / Email / SMS	
Digital Pan / Tilt / Zoom	YES	
Minimum Web Browsing Requirements	• Pentium 4 CPU 1.3 GHz or higher, or equivalent AMD • 256 MB RAM • AGP graphics card, Direct Draw, 32MB RAM • Windows 7, Vista & XP, DirectX 9.0 or later • Internet Explorer 7.x or later	

* The specifications are subject to change without notice.

** Dimensional tolerance: ± 5mm


APPENDIX 2 BIT RATE TABLE FOR REFERENCE

The data below is for reference only.

The bit rates listed here may vary depending on the resolution, image quality & frame rate you choose, the complexity of your monitoring area, and how often the moving objects show in your monitoring area.

Testing Environment

- Place: Office Entrance
- Network translation: H.264
- Camera type: Megapixel camera



Static: No one coming in and out



Dynamic: One or two people coming in and out


Resolution	Quality	Frame Rate	(Dynamic) kbps	(Static) kbps
SXGA	Best	FULL	3253	3216
	High		2375	2160
	Normal		1571	1266
	Basic		1465	873
VGA	Best		2010	1261
	High		1042	1034
	Normal		685	572
	Basic		457	350
QVGA	Best		646	366
	High		482	350
	Normal		302	286
	Basic		168	161
SXGA	Best	1/4	1163	1076
	High		989	715
	Normal		855	534
	Basic		719	443
VGA	Best		789	571
	High		451	447
	Normal		349	237
	Basic		217	165
QVGA	Best		269	147
	High		182	131
	Normal		164	113
	Basic		97	71

Resolution	Quality	Frame Rate	(Dynamic) kbps	(Static) kbps
SXGA	Best	1/15	581	374
	High		405	342
	Normal		487	248
	Basic		337	141
VGA	Best		358	79
	High		201	63
	Normal		180	28
	Basic		92	15
QVGA	Best		111	84
	High		99	68
	Normal		97	54
	Basic		58	42


APPENDIX 3 POE CONNECTION

This device supports PoE (Power-over-Ethernet), developed by the IEEE802.3af task force, and power can be supplied over the same network (Ethernet) cable as the one used to connect to Internet. No power cable is needed. Below shows two examples of POE application for reference.

- When your router / hub supports POE connection



- When your router / hub doesn't support POE connection (An optional POE connector required)




APPENDIX 4 API ID APPLICATION FOR SMS MESSAGING

To allow the camera automatically sending a text message when an event happens, you need to apply an API ID from Clickatell, one mobile messaging company, first.

Note: The SMS messaging is not totally free. You will be charged starting from the 11th message.


Please follow the steps below for application.

Step1: Go to <http://www.clickatell.com/login.php>. In “New Customers”, select “Clickatell Central (API)” from the drop-down list.



Step2: Fill in your information to create an account, and click “CONTINUE”.


Note: Note down the user name and password, and the mobile phone number you specified here for SMS notification setting later.



Step2: When the account is created, the system will automatically send an Email to your specified Email address and ask you to activate your account.

Click the link in the Email to complete account activation, and enter the login page as follows.
Enter the password you set, and click “Login”.

My Account Login



Customer Login

Existing Clickatell account holders can select their product and login below. Note, username & password are CASE sensitive.

Select Product: Clickatell Central (API)

Username:

ClientID:


Password:

[Lost password?](#)

Enter the password you set to log in.

Step3: Enter the mobile phone number (including your country code) you want the text message to be sent, and click “SEND ACTIVATION CODE”. The system will send an activation code to that number for verification.

Check if you receive a text message from Clickatell.



Verify your Mobile Number

For security reasons you are required to verify your mobile number before you can use non-test SMS messages.


Your activation code will be sent to

If this is not your number, please retype your mobile number in the box above and click the "Send Activation Code" button.

Enter your activation code here:

Enter your mobile phone number, including your country code.

Step4: Go back to Clickatell, and click the tab “Manage my Products”.
Then, select “HTTP” from the drop-down list “My Connections”.



Manage my Products

Central Home | My Settings | **Manage my Products** | Billing | Message Reports | Help

Manage my Products


My Connections:

Add Connection

HTTP

Select "HTTP".

Step5: In “Add HTTP API”, enter a descriptive name for this service, and make sure the dial prefix is correct and callback type is “HTTP GET”. Then, click “Submit”.



Add HTTP API - Bold Items Required

Name:

IP Lock Down:

Dial Prefix:

Callback Type:

Callback Url:


Callback Username:

Callback Password:

Minimum information required

Step5: You will get an API ID as follows.

Note: Note down the API ID for SMS notification setting later.




Name	Type	API ID	Dialing Code
IP_SMS	SMTP API	3218637	886 Taiwan
IP_MSG	HTTP	3220810	886 Taiwan

1 to 2 of 2

APPENDIX 5 Q&A

For more details about Q&A, please visit our official website: www.eagleeyesccv.com/supp_QnA.aspx.

Question	Answer
<p>I can connect to this camera in my house or office where it's installed with wireless network.</p> <p>But when I leave my house or office, I can't connect to it from my mobile phone (with 3G network), or other PC (connected to Internet). Why?</p>	<p>You didn't configure this camera to Internet, but only in LAN.</p> <p>Please follow the steps in the advanced network setup guide downloadable from www.surveillance-download.com/user/m357a.swf to complete network configurations, or it's recommended for you to check with your local installer or reseller for this service because it's usually hard for a person who doesn't have network knowledge to set network configurations.</p>
<p>My live images are not fluent. Why?</p>	<p>Image fluency could be affected by the local network upload bandwidth, router efficiency, client network download bandwidth, complexity of live view, and more.</p> <p>(Recommended) To have the best image fluency, select QVGA; to have the best image quality, select "SXVGA" based on the model you have; to have normal image fluency and quality, select "VGA".</p>
<p>The live video keeps flickering. Why?</p>	<p>Please try adjusting the power line frequency to "60 Hz" or "50 Hz" for the camera.</p> <p>For iPhone users, access the camera, and select " on the top right corner to enter IPCAM Configuration page. Then, go to "Advance Setup" → "Camera" to change setting.</p> <p>For access from Internet Explorer, log into the camera, and select "Config." → "Camera" → "Camera".</p>

APPENDIX 6 RECORDING TIME TABLE

Below shows the estimated total recording time for each recording resolution.

The recording time per resolution is the average value collected from the both alarm trigger conditions indicated in “Testing Environment”, and is for reference only.

The time may vary depending on the resolution, image quality & frame rate you choose, the complexity of your monitoring area, and how often the moving objects show in your monitoring area.

Testing Environment

- Place: Office
- Monitoring area: 1.5 meters away from the camera
- Alarm trigger conditions:
 - (1) One person walks by the monitoring area and leaves immediately.
 - (2) Two persons walk by the monitoring area. One goes away immediately, and the other one stays a while and goes away.

Recording Resolution	SXGA	VGA	QVGA
Recording time (second)	25	115	211

網路攝影機系列

操作指南

在使用本機前請務必詳細閱讀安全須知及操作說明，並保存此手冊以備後續參考。

安全須知



本公提供的所有無鉛產品皆符合歐盟有害物質使用限制指引 (Restriction of Hazardous Substances, (RoHS))，意即本公司的生產流程與產品均嚴格遵守無鉛守則，而且不包含該指引內提供的任何有害物質。



此劃叉的滾輪垃圾筒圖示代表在歐盟境內，本產品於丟棄時必須另行收集。此原則適用於您的產品與任何標有此圖示的週邊設備。請勿隨意丟棄這些產品。請洽詢您當地的經銷商，以得知回收此設備的程序。



本裝置符合低功率電波輻射性規範，請使用者遵循相關電信法規。

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device must not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

FCC Caution:

- Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.
- All external cables connecting to this basic unit must be shielded.
For cables connecting to PCMCIA cards, see the option manual or installation instructions.

商標聲明

iPad®、iPhone® 是 Apple Inc. 的註冊商標。

Android™ 是 Google Inc. 的商標。此商標的使用必須依 Google Permissions 的規定使用。

Microsoft®、Windows® 和 Internet Explorer® 是 Microsoft Corporation 在美國和 / 或其他國家的註冊商標。

Opera 為 Opera Software 的商標或註冊商標。

免責聲明

本公司保留可隨時修改或刪除說明書內容的任何權利。本公司不保證此說明書的內容完全無誤、完整或實用。此說明書內容更改以實際產品為準，將不另行通知。

本產品不支援待機模式

MPEG-4 授權

THIS PRODUCT IS LICENSED UNDER THE MPEG4 VISUAL PATENT PORTFOLIO LICENSE FOR THE PERSONAL AND NON-COMMERCIAL USE OF A CONSUMER FOR (i) ENCODING VIDEO IN COMPLIANCE WITH THE MPEG4 VISUAL STANDARD ("MPEG-4 VIDEO") AND/OR (ii) DECODING MPEG4 VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL AND NON-COMMERCIAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED BY MPEG LA TO PROVIDE MPEG4 VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION INCLUDING THAT RELATING TO PROMOTIONAL INTERNAL AND COMMERCIAL USES AND LICENSING MAY BE OBTAINED FROM MPEG LA, LLC. SEE [HTTP://WWW.MPEGLA.COM](http://www.mpegla.com).

GPL 授權



This product contains codes which are developed by Third-Party-Companies and which are subject to the GNU General Public License ("GPL") or the GNU Lesser Public License ("LGPL").

The GPL Code used in this product is released without warranty and is subject to the copyright of the corresponding author.

Further source codes which are subject to the GPL-licenses are available upon request.

We are pleased to provide our modifications to the Linux Kernel, as well as a few new commands, and some tools to get you into the code. The codes are provided on the FTP site, and please download them from the following site or you can refer to your distributor:

http://download.dvrtw.com.tw/GPL/076D_Series/arm-linux-2.6.tar.gz

目錄

1. 產品概述.....	5
1.1 產品特點.....	5
1.2 包裝明細.....	5
1.3 線路概觀.....	5
2. 使用 INTERNET EXPLORER 登入攝影機.....	6
2.1 登入攝影機.....	6
2.2 控制面板簡介.....	6
2.3 DPTZ 操作.....	8
2.4 錄影事件搜尋與回放.....	9
3. 攝影機設定.....	10
3.1 系統設定選單.....	10
3.2 網路設定.....	11
3.2.1 網路設定.....	11
3.2.2 QoS.....	11
3.2.3 DDNS.....	11
3.2.4 網路對時.....	12
3.2.5 影像上傳.....	12
3.2.6 郵件管理.....	12
3.2.7 SMS.....	13
3.2.8 過濾器.....	14
3.2.9 UPnP / Bonjour.....	14
3.2.10 RTP.....	15
3.3 攝影機設定.....	16
3.3.1 攝影機設定.....	16
3.3.2 影像設定.....	16
3.3.3 顏色設定.....	17
3.3.4 進階設定.....	17
3.4 定時錄影.....	18
3.4.1 錄影.....	18
3.4.2 定時錄影.....	18
3.5 儲存裝置.....	18
3.5.1 記憶體.....	18
3.6 觸發設定.....	19
3.6.1 觸發設定.....	19
3.7 常用設定.....	20
3.7.1 常用設定.....	20
3.7.2 時間設定.....	21
3.7.3 系統日誌.....	21
3.7.4 連線使用者.....	22
3.7.5 權限管理.....	22
3.7.6 Google 地圖.....	23
3.7.7 系統維護.....	23
韌體更新.....	23
附錄 1 產品規格.....	25
附錄 2 傳輸速度參照表.....	26
附錄 3 連接 POE 功能.....	28
附錄 4 如何申請簡訊通知功能的應用程式介面識別碼.....	29
附錄 5 常見問題集.....	31
附錄 6 錄影時間表.....	32

1. 產品概述


1.1 產品特點

- 使用 **iPhone / iPad**，快速完成網路設定
- **130 萬畫素**的 LIVE MOS 感應元件並支援 **HDTV 720p**，讓使用者能看到更細微的內容
- 支援 **ONVIF** 功能，簡化系統整合
- 支援 **Power-over-Ethernet** 功能 (POE)，節省用電量與重新佈線的成本
- 支援**外接警報裝置**
- 內建 35 顆 IR LED 燈，提供**夜間監控**功能
- **遠端監控**
 - 可由 **iPhone & iPad**，以及 Windows® 作業系統的 **Internet Explorer®** 進行遠端監控

1.2 包裝明細

<input type="checkbox"/> 網路攝影機	<input type="checkbox"/> 攝影機支架	<input type="checkbox"/> 快速設定指南 (使用 iPhone / iPad)
--------------------------------	--------------------------------	--

1.3 線路概觀



顏色	線路	說明
--	電源線	連接 DC12V 的電源變壓器。 註：電源變壓器需自行選購。
--	RJ45 網路線	連接隨附的延長轉接頭，再接上您自備的合適長度網路線。
黑色 & 棕色	接地線	接地線，用來重設預設值或是連接外部裝置。
黃色	Alarm-in 訊號線	用於連接外部警報裝置。詳情請參閱您安裝的警報裝置說明書。
粉色	Alarm-out 訊號線	用於連接外部警報裝置。詳情請參閱您安裝的警報裝置說明書。 <div></div>
紅色	重設線	移除重設線上的絕緣外殼，之後將兩線相碰觸後，重設所有參數回原廠設定值，包括 IP 位址。 註：在碰觸兩線前請先拔除攝影機電源，重設完成後再重新上電。

2. 使用 INTERNET EXPLORER 登入攝影機

視您的使用環境而定，您可以使用 Microsoft® Internet Explorer® 登入此攝影機，或者在 iPhone / iPad / Android 行動裝置安裝本公司研發的行動小程序 EagleEyes 來進行登入。

註：如需得知使用 iPhone / iPad / Android 行動裝置登入此攝影機的詳細資訊，請參閱 <http://www.eagleeyesccv.com>。

在使用此攝影機之前，請先確認您已做好網路設定，而且網路連線正常。

如需得知網路設定的相關資訊，請參閱：

- 隨附攝影機提供的「快速設定 (使用 iPhone / iPad)」－ 若您有 iPhone / iPad，而且您是使用無線網路來上網
- 「進階網路設定」，可從 www.surveillance-download.com/user/m357a.swf 下載－ 若您不是使用無線網路來上網

2.1 登入攝影機

步驟 1：開啓您的網路瀏覽器，然後在位址列輸入 http://IP 位址:埠號。

舉例來說，若 IP 位址為 60.121.46.236 且埠號為 888，請在 URL 網址列中輸入 http://60.121.46.236:888，然後按 Enter。

步驟 2：在登入頁面中，輸入預設的使用者名稱和密碼，然後輸入下圖顯示的驗證碼。接著，按 [LOGIN] 登入。

步驟 3：設定精靈隨即啓動。

- 若要離開精靈並直接登入攝影機，請按 [關閉]。
- 若不要在每次登入時都啓動精靈，而是直接進入攝影機畫面，請按 [登入時不啓動精靈]。

註：若系統要求您安裝「VLC player」、「Software」和「H264 Streaming Viewer」，請同意完成安裝。

步驟 5：登入成功後就會看到即時畫面。

2.2 控制面板簡介

註：視登入權限與使用的型號不同，可使用的按鈕也會不同。




功能	圖示	使用者權限	說明
即時影像		系統使用者 / 超級使用者 / 一般使用者 / 訪客	切換到即時影像頁面。
備份		系統使用者 / 超級使用者	進入事件錄影清單，搜尋要播放的錄影檔案。 詳情請參閱第 9 頁的「2.4 錄影事件搜尋與回放」。
DPTZ*		系統使用者 / 超級使用者 / 一般使用者	切換到 DPTZ 設定頁面。 詳情請參閱第 8 頁的「2.3 DPTZ 操作」。
系統設定		系統使用者	切換到系統設定頁面；使用「系統使用者」和「超級使用者」登入時看到的機能是不同的。 詳情請參閱第 10 頁的「3.1 系統設定選單」。
即時播放器	--	系統使用者 / 超級使用者 / 一般使用者 / 訪客	從下拉式清單選擇播放軟體： <div> <div>■ H.264 / MPEG-4 / Motion JPEG</div> <div>■ QuickTime</div> <div>QuickTime 是 Apple 公司的多媒體播放軟體。在選取 QuickTime 之前，您必須先將 QuickTime 安裝到您的作業系統。選取 QuickTime 後，系統會提示您輸入使用者名稱和密碼來登入攝影機。</div> <div>■ VLC</div> </div>
影像品質	--	系統使用者 / 超級使用者 / 一般使用者	按住並拖曳滑桿來選取影像畫質：低 / 一般 / 高 / 最好。
影像規格	--	系統使用者 / 超級使用者 / 一般使用者	從下拉式選單選取影像解析度： <div> <div>■ SXGA (1280 x 1024)</div> <div>■ VGA (640 x 480)</div> <div>HD720P (1280 x 720)</div> <div>QVGA (320 x 240)</div> </div>
即時影像顯示方式		系統使用者 / 超級使用者 / 一般使用者	
全螢幕			按此鈕來全螢幕顯示影像。 若要離開全螢幕顯示，請按一下鍵盤上的 [Esc] 鍵。 當選取的影像規格為 <i>SXGA / HD720P / VGA</i> 時，才能使用此功能。
CIF 調整大小			QVGA 影像大小已被重新調整以符合螢幕尺寸。 當選取的影像規格為 <i>QVGA</i> 時，才能使用此功能。
原來大小			目前影像大小與選取的影像規格相符。 當選取的影像規格為 <i>SXGA / HD720P</i> ，才能使用此功能。
符合螢幕大小			選取的影像大小已被重新調整以符合螢幕尺寸。 當選取的影像規格為 <i>SXGA / HD720P</i> ，才能使用此功能。
拉框檢視			按住即時影像左下角的可移動方框來移動畫面。 當選取的影像規格為 <i>SXGA / HD720P</i> ，才能使用此功能。
快照		系統使用者 / 超級使用者 / 一般使用者	截取即時影像的畫面；影像檔會顯示於新視窗，按右鍵點選圖像，將圖像儲存在您指定的位置。
警報發出		系統使用者 / 超級使用者 / 一般使用者	強制警報裝置啟動。例如，若您連接了一台蜂鳴器，一旦按下此鈕，就算沒有發生警報，警鳴器也會放聲大響。



2.3 DPTZ 操作

此攝影機擁有所謂的數位 PTZ 功能 (之後都稱「DPTZ」)，讓使用者能看到更清楚的畫面。

步驟 1：按 [DPTZ] 顯示 DPTZ 控制面板。




步驟 2：選擇您想使用的功能：

功能	圖示	說明
解析度	--	選擇 DPTZ 功能的影像解析度，包括 VGA 及 QVGA 選項。
快照		截取即時影像的畫面；影像檔會顯示於新視窗，按右鍵點選圖像，將圖像儲存在您指定的位置。
警報發出		強制警報裝置啟動。例如，若您連接了一台蜂鳴器，一旦按下此鈕，就算沒有發生警報，警鳴器也會放聲大響。

2.4 錄影事件搜尋與回放

此攝影機最多可以儲存三筆警報錄影事件。

註：若想要儲存更多錄影資料，建議可搭配相同的 NVR 使用。



	往前一小時 / 往後一小時	往前或往後一小時，例如 11:00 ~ 12:00 或 14:00 ~ 15:00，並開始播放在該時段最早的錄影資料。
	快轉	增加快轉的速度。點一次以 4 倍的速度快轉，兩次 8 倍，以此類推，最高速為 16 倍。
	倒轉	增加倒轉的速度。點一次以 4 倍的速度倒轉，兩次 8 倍，以此類推，最高速為 16 倍。
	播放	播放目前的錄影片段。
	暫停	暫停影片播放。
	停止	停止影片播放。
	單張播放	在暫停影片播放時，按一下格放前進一張影像。
	聲音	必要時，點一下關閉回放畫面內的錄音播放關閉，再點一下即可恢復。
	備份	將目前播放的錄影片段儲存在電腦的指定位置。 下載的影片只能使用我們專用的影片播放程式開啟。您可以從 [常用設定] → [系統維護] 下載此程式，或者從隨附的光碟裡取得。

3. 攝影機設定

使用者可以透過 Internet Explorer 登入攝影機進行更多設定。

3.1 系統設定選單

按 [系統設定] 進入設定頁面。

系統設定選項分成六個主要目錄選單：「網路設定」、「攝影機設定」、「定時錄影」、「儲存裝置」、「觸發設定」和「常用設定」。

- 如需得知「網路設定」的相關資訊，請參閱第 11 頁的「3.2 網路設定」。
- 如需得知「攝影機設定」的相關資訊，請參閱第 16 頁的「3.3 攝影機設定」。
- 如需得知「攝影機設定」的相關資訊，請參閱第 18 頁的「3.4 定時錄影」。
- 如需得知「儲存裝置」的相關資訊，請參閱第 18 頁的「3.5 儲存裝置」。
- 如需得知「觸發設定」的相關資訊，請參閱第 19 頁的「3.6 觸發設定」。
- 如需得知「常用設定」的相關資訊，請參閱第 20 頁的「3.7 常用設定」。

主選單	子選單	說明
網路設定	網路設定	設定網路連線。
	頻寬控制	啟動頻寬限制。
	DDNS	若使用的網路類型為 PPPOE 或 DHCP，需輸入 DDNS 資訊。
	網路對時	將攝影機的時間和網路電腦系統同步化。
	影像上傳	若在 [觸發設定] → [觸發設定] 裡選擇 [FTP]，需在此輸入 FTP 資訊。
	郵件管理	若在 [觸發設定] → [觸發設定] 裡選擇 [E-Mail]，需在此輸入 E-Mail 資訊。
	簡訊通知	若在 [觸發設定] → [觸發設定] 裡選擇 [SMS]，需在此輸入簡訊資訊。
	過濾器	選擇要允許或封鎖能登入此攝影機的 IP 位址。
	UpnP	* 適用於 Windows 操作系統 允許在相同網域下的其他裝置能偵測得到這隻攝影機並可快速使用。
	Bonjour	* 適用於 Mac 操作系統 Bonjour 是一項能夠在區網自動設定並偵測特定的網路服務。
	RTP	如使用網頁瀏覽器及 Video Viewer 之外的媒體平台，進行遠端監控，須設定影像傳輸速率的參數。
攝影機設定	攝影機設定	1. 設定攝影機名稱。 2. 變更攝影機名稱在螢幕上顯示的位置。
	影像設定	調整不同影像格式的相關影像設定。
	顏色設定	調整色彩效能。
	進階設定	調整攝影機參數。
定時錄影	錄影	設定錄影功能。
	定時錄影	預約外接警報錄影時間。
儲存裝置	SD 記憶卡	查看記憶卡容量，還可清除所有錄影資料。

主選單	子選單	說明
觸發設定	觸發設定	<ol style="list-style-type: none"> 1. 啟動 / 關閉 位移偵測功能。 2. 設定位移偵測範圍。 3. 設定攝影機在遇到各個事件時的回應。
常用設定	常用設定	<ol style="list-style-type: none"> 1. 選擇語言。 2. 查看攝影機的 MAC 位址。 3. 設定攝影機在指定時間過後自動上鎖禁止存取。 4. 啟動 / 關閉 LED 狀態指示燈。
	時間設定	設定日光節約時間和目前的時間。
	系統日誌	查看系統事件日誌。
	連線使用者	查看目前的線上使用者資訊。
	權限管理	<ol style="list-style-type: none"> 1. 建立具有不同存取權限的使用者帳號。 2. 修改或刪除現有使用者帳號。
	Google 地圖	查看目前攝影機所在位置。
	系統維護	<ol style="list-style-type: none"> 1. 查看目前的韌體版本與升級。 2. 複寫系統相關設定。 3. 重新啟動攝影機。 4. 下載影片播放器播放影片。

3.2 網路設定

3.2.1 網路設定

依您的網路類型而定，在此可設定攝影機的網路設定。

詳情請參閱「進階網路設定」，請由 www.surveillance-download.com/user/m357a.swf 下載。

區域網路設定

IP類型: ☒ 固定IP ☐ PPPoE ☐ DHCP

IP位址: 60.250.165.98

閘道: 60.250.165.97

網路遮罩: 255.255.255.0

埠號: 80

DNS1: 168.95.1.1

DNS2: 139.175.55.244

MAC 位址: 00:0E:53:E5:EB:BE

3.2.2 QoS

頻寬控制設定 (Quality of Service)，是一種控制機制，它提供了針對不同使用者或者不同資料流採用相應不同的優先順序，或者是根據應用程式的要求，保證資料流的效能達到一定的水準。勾選 [開啓]，設定最大上傳速率，設定範圍可從每秒 256 位元 到 10240 位元。

頻寬控制設定

頻寬控制: ☒ 開啓 ☐ 關閉

介面: Ethernet

最大上傳速率: 4096 kbps

3.2.3 DDNS

若在 [網路設定] 選取的網路類型為 [PPPOE] 或 [DHCP]，請選擇 [開啓]。

詳情請參閱「進階網路設定」，請由 www.surveillance-download.com/user/m357a.swf 下載。

DDNS設定

DDNS: ☒ 開啟 ☐ 關閉

系統名稱: default

主機名稱: MAC000e5320d47c .ddns.eagleeyes.tw

E-Mail: manager@tech.com

儲存設定

重新載入

3.2.4 網路對時

網路對時是用來同步化攝影機和網路電腦系統的時間。

網路對時設定

GMT: (GMT+08:00) Taipei

NTP伺服器: tock.stdtime.gov.tw

同步週期: 每天

主機時間: 2011-12-09 20:56:21

時間同步

儲存設定

重新載入

功能	說明
GMT	只要選好時區，網路攝影機就會自動調整系統的本機時間。
NTP 伺服器	您可以選擇保留預設的 SNTP 伺服器（例如，tock.stdtime.gov.tw），或者改成您知道的其他伺服器。
同步週期	選擇“每天”將每天的網路時間同步到攝影機，或選擇“無”來關閉此功能。
時間同步	按此按鈕後，網路攝影機的時間即會與網路時間同步。

3.2.5 影像上傳

輸入詳細的 FTP 資訊，然後按【儲存】確認。在【觸發設定】→【觸發設定】選取【FTP】時，則會套用設定於此的功能。

影像上傳設定

帳號: manager

密碼: ●●●●●●

主機名稱: 192.168.2.32

埠號: 21

路徑: upload

儲存設定

測試

重新載入

3.2.6 郵件管理

輸入詳細的電子郵件資訊，然後按【儲存】確認。在【觸發設定】→【觸發設定】選取【E-Mail】時，則會套用設定於此的功能。

SMTP設定

郵件主機名稱: ms.tech.com

埠號: 465

寄件人信箱: manager

SSL加密: ☒ 是 ☐ 否

密碼驗證: ☒ 是 ☐ 否

帳號: manager

密碼: ●●●●●●●●

儲存設定

測試

重新載入

收件人信箱清單

收件人信箱:

新增 修改 刪除

收件人	收件人信箱
boss	boss@tech.com

功能	說明
郵件主機名稱	輸入您從電子郵件系統供應商取得的 SMTP 伺服器位址。
埠號	輸入您從電子郵件系統供應商取得的埠號。若沒有填寫此欄，則會預設使用 25 做為傳送郵件的埠號。
寄件人信箱	輸入寄件人名稱。
SSL 加密	如果您是使用 SSL 加密協定來防止重要的資訊遭到攔截，請選擇“是”。
密碼驗證	有些郵件伺服器需要驗證密碼。請輸入【帳號】和【密碼】。
收件人信箱	新增指定收件人的電子郵件位址。
測試	當您輸入完所有資料，請點選“測試”來確認是否可以收到訊息。

3.2.7 SMS

註：開啓此功能前，須先從簡訊通知系統供應商 **Clickatell**，取得應用程式介面辨別碼。簡訊通知功能的費用自第十一封簡訊起算，詳請參閱第 29 頁的「附錄 4 如何申請簡訊通知功能的應用程式介面識別碼」。

設定簡訊通知系統需輸入詳細資訊，然後按【儲存】確認。在【常用設定】→【觸發設定】選取【FTP】時，您所輸入的資訊則會套用設定於此的功能。

簡訊通知

簡訊通知設定

系統商: clickatell

帳號: tech

密碼:

應用程式介面識別碼: 3281378

接收電話號碼: +886

發送間隔: 15 分鐘

訊息內容: [192.168.1.10] unauthorized access!

更多

重新計數

包含主機名稱或是IP

儲存設定

測試

重新載入

功能	說明
系統商	簡訊通知系統商為 Clickatell 。
帳碼 / 密碼	輸入帳號密碼。
應用程式介面辨別碼	輸入應用程式介面辨別碼。
接收電話號碼	點選【新增】輸入電話號碼。完整號碼須包含國碼，最多可新增五組號碼。
發送間隔	設定簡訊發送間距時間（分），可選擇 0 / 15 / 30 / 60 分鐘。
重新計數	點選此鍵更新簡訊通知功能，之後的簡訊通知將依您所設定的間隔時間傳送。
訊息內容	輸入您想傳送的簡訊內容。(至多七十個字元)
測試	測試您的簡訊通知設定是否正確，按一下【測試】立即傳送訊息至手機。 註：此測試功能並非免費提供，簡訊通知費用將依各地費率計費。

3.2.8 過濾器

選擇要允許或封鎖能登入此攝影機的 IP 位址，然後按 [儲存] 確認。

過濾器設定

錯誤次數：

錯誤封鎖時間： 分鐘

回應要求：☒ 不封鎖 ☐ 封鎖

IP/MAC過濾器設定

IP/MAC過濾：☒ 開啓 ☐ 關閉

IP/MAC過濾方法：☒ 允許 ☐ 拒絕

IP/MAC過濾條件

條件：

192.168.1.23

功能	說明
■ 過濾器設定	
錯誤次數	設定登入失敗的最大可接收次數。登入失敗次數達到設定上限後，該 IP 位址就會被封鎖。
錯誤封鎖時間	設定被封鎖的 IP 位址，要被封鎖多久時間。
回應要求	選擇 [不封鎖] 讓其他使用者可以 ping 到此網路攝影機的 IP 位址，而選擇 [封鎖] 則可拒絕回覆 ping 指令。
■ IP/MAC 過濾設定	
IP/MAC 過濾	選擇要啓用或停用過濾器功能。
IP/MAC 過濾方法	若選擇 [開啓]，請確認要允許或拒絕指定的 IP 位址。
■ IP/MAC 過濾條件	
條件	<div>• 若要新增 IP 位址，請在 [條件] 輸入 IP 位址，然後按 [新增]。</div> <div>• 若要刪除現有 IP 位址，先點選要刪除的位址，然後按 [刪除]。</div>

3.2.9 UPnP / Bonjour

UPnP 為 Universal Plug and Play (通用隨插即用) 的縮寫，即允許此裝置可以在家用與企業的網路環境中被偵測與使用，且可簡化安裝與設定流程，且只適用在 Windows 作業系統。

Bonjour 在功能面和 UPnP 完全一樣，不過 Bonjour 只適用在 Mac 作業系統。

➤ UPnP

UPnP設定

UPnP：☒ 開啓 ☐ 關閉

裝置名稱：

➤ Bonjour

Bonjour設定

Bonjour：☒ 開啓 ☐ 關閉

裝置名稱：

勾選 [開啓] 讓此攝影機可以在同網域下被偵測到，並將您的 [裝置名稱] 設定為好記的名稱。

啓用此功能後，其他與此攝影機位在相同網域下的電腦就可在 [網路上的芳鄰] 搜尋到此攝影機。

➤ 在 Windows 作業系統環境下，請將 [網路芳鄰] 和 [裝置名稱] 皆設定為好記的名稱。

➤ 在 Mac 作業系統環境下，請將 “” (finder) 或是 “Bookmark” 及 [裝置名稱] 皆設定為好記的名稱。

連按兩下找到的攝影機，即可快速開啓網路瀏覽器並進入登入頁面。

14

埠號轉址設定 (前提須支援 UPnP)

依此功能，您不需要額外進入 Router，也可設定埠號轉址。

詳情請參閱「進階網路設定」，請由 www.surveillance-download.com/user/m357a.swf 下載。

註：在使用此功能之前，請先確認您的 Router 有支援 UPnP，而且此功能已開啓。如果沒有，您就還是要另外進入 Router 設定埠號轉址。

將 [埠號轉址] 設爲 [開啓] 後，若沒有特別指定 [路由器 IP] 或 [HTTP 埠號]，系統就會自動偵測一組 IP 位址或指定一個埠號給您使用。

埠號轉址設定

埠號轉址：☒ 開啓 ☐ 關閉

路由器IP: (區域網路IP位址)

HTTP 埠號:

HTTPS 埠號:

*如果設定空白或0，則由系統自動設定埠號

註：當設定成功時，您會在此頁面看到分配給此攝影機的 IP 位址和埠號。

3.2.10 RTP

RTP (Real-time Transport Protocol) 爲一網路協定，用以管理多點傳播的即時傳輸，VLC 播放器即爲一例。

在使用媒體播放器進行遠端登入時，請先確認您的播放器有支援 RTP

註：如欲關閉遠端登入，先點選媒體播放器的停止鍵，然後關閉程式。此可確認伺服器收到停止命令，也可避免重複的資料傳輸。

RTP

埠號範圍

起始埠號:

終點埠號:

多點傳播

H264

解析度	位址	埠號
SXGA / HD720P	239.101.101.102	9000
VGA	239.101.101.103	9000
QVGA	239.101.101.104	9000
QQVGA	239.101.101.105	9000

MPEG4

解析度	位址	埠號
SXGA / HD720P	239.101.102.102	9000
VGA	239.101.102.103	9000
QVGA	239.101.102.104	9000
QQVGA	239.101.102.105	9000

JPEG

解析度	位址	埠號
SXGA / HD720P	239.101.103.102	9000
VGA	239.101.103.103	9000
QVGA	239.101.103.104	9000
QQVGA	239.101.103.105	9000

存活時間 (TTL):

功能	說明
■ 埠號範圍	
RTP 的埠號範圍有限，且起始埠號和終點埠號之間須保持 100 組的埠號。	
起始埠號	起始埠號的範圍爲 1024 到 65434。
終點埠號	終點埠號的範圍爲 1124 到 65534。
■ 多點傳播	
H264 / MPEG4 / JPEG 傳輸的位址與埠號	設定多點傳輸內個別影像格式 (H264/ MPEG4/ JPEG) 的位址與埠號。 位址的設定範圍 224.0.0.1 ~ 239.255.255.255。 埠號必須爲偶數。

功能	說明
存活時間 (TTL)	存活時間的範圍為 1 到 255，當存活時間歸零就會斷線。

3.3 攝影機設定

3.3.1 攝影機設定

重新命名攝影機裝置和變更裝置名稱在螢幕顯示位置於左上 / 右上 / 左下 / 右下。

攝影機

攝影機設定

名稱: IPCAM

位置: 下-右

儲存設定

重新載入

3.3.2 影像設定

在不同影像格式下變更影像相關設定

- 畫質與畫面清晰度相關。
- FPS 表示影像的流暢度。FPS 的值越大，影像呈現越順暢。
- Max Bit Rate 表示在選定的影像格式和像素內，資料所能傳輸的最大限度。

註：QQVGA 為手機監控專用格式。

影像設定

系統類型設定

電源頻率: 50

Hz

H264

解析度	品質	FPS	最大 Bit 速率
HD1080P	高	30	8000
/ HD720P	高	30	8000
VGA	高	30	3000
QVGA	高	30	3000
QQVGA	高	30	3000

MPEG4

解析度	品質	FPS	最大 Bit 速率
HD1080P	高	15	8000
/ HD720P	高	30	8000
VGA	高	30	3000
QVGA	高	30	3000
QQVGA	高	30	3000

JPEG

解析度	品質	FPS
HD1080P	高	30
/ HD720P	高	30
VGA	高	30
QVGA	高	30
QQVGA	高	30

儲存設定

重新載入

3.3.3 顏色設定

調整色彩效能：亮度、對比度、色度和飽和度。按住滑桿做調整即可預覽色彩變更。

若要回復預設值，請按 [回到預設值]。



3.3.4 進階設定

視需求調整攝影機相關參數。



項目	說明
快門速率	依您的需求設定快門速率。 選項有：1/10、1/30、1/15、1/6、1 和 2 秒。
鏡射	依您需求的架設環境，點選此功能後，畫面將水平旋轉。
翻轉	依您需求的架設環境，點選此功能後，畫面將旋轉 180 度。
消除雜音	依您需求的架設環境，按住並拖曳滑桿來選取在黑暗環境下的適當參數。等級從 0 ~ 10，級數越高，雜音越少。
紅外線控制	點選 [自動] 用來開啓紅外線 LED 在遇夜間或黑暗環境時自動啓動。選擇 [開啓] 或 [關閉] 啓動紅外線 LED 功能。
白平衡*	白平衡的設定是爲了表現出當時的色溫，並且讓原本白色的東西，在不同色溫下仍看到白色。 選項有：自動、白燈、冷光、日光、陰天及遮陽。
清晰度	藉由調整相機光圈大小及影像邊緣銳利化，可以讓影像的小細節看起來更清楚。 按住並拖曳滑桿來選取適當參數。等級從 0 ~ 100，級數越高，影像越清晰。

3.4 定時錄影

3.4.1 錄影

在 [定時錄影設定] 下：

- 啟動或停用所有錄影功能。將 [啟動] 設成 [否] 時，就會停用所有的錄影功能。
- 選擇是否要在儲存裝置容量滿時覆蓋之前的檔案繼續錄下去。
- 選擇錄影影像解析度。

註：選擇越高的解析度，影片的畫質就會越好，但記憶體就會消耗的越快。

錄影設定

開啟：☒ 是 ☐ 否

覆寫：☒ 是 ☐ 否

錄音：☒ 是 ☐ 否

錄影解析度：

VGA

儲存設定

重新載入

3.4.2 定時錄影

若要設定警報，請選擇啟動錄影的日期與時間。

註：警報功能請務必選擇開啟以使錄影功能正常進行。

外部警報

開啟：☐ 是 ☒ 否

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
SUN																								
MON																								
TUE																								
WED																								
THU																								
FRI																								
SAT																								

儲存設定

重新載入

3.5 儲存裝置

3.5.1 記憶體

在 [記憶體]，您可以查看可錄影的剩餘容量，還可選擇清除所有儲存在記憶體中的錄影資料。

註：已記錄的資料將會在您按重設鍵後及重新開啓攝影機時被移除。

此攝影機最多可以儲存三筆警報錄影事件。

註：若想要儲存更多錄影資料，建議可搭配相同的 NVR 使用。

註：欲知不同錄影解析度下能錄製的總預計時間，請參閱第 32 頁「附錄 6 錄影時間表」。

記憶體設定

檔案系統：RAMDISK

總容量：10.00 MB

使用容量：

10.00 MB (100.00%)

清除

重新載入

3.6 觸發設定

3.6.1 觸發設定

設定在發生警報或位移偵測後，攝影機的后續回應動作。

偵測

警報觸發：

開啟

移動觸發：

開啟

警報持續時間：

10 秒

移動偵測

動作

E-Mail:

☐外部警報

☐移動

FTP:

☐外部警報

☐移動

SMS:

☐外部警報

☐移動

警報發出:

☒外部警報

☐移動

錄影設定:

☐外部警報


聲音警報:

☒手動警報發出

儲存設定

重新載入

◆ 偵測

項目	說明
警報	視您連接的警報裝置而定，選擇 [N.O.] 或 [N.C.]。
移動	<div>開啓或關閉位移偵測功能。</div> <div>若將影像格式設為 [Motion JPEG]，就無法使用位移偵測功能。</div> <div>選取 [開啓] 後，按 [移動偵測] 進入移動偵測區域頁面如下：</div> <div><div><div>偵測設定</div><div><div>靈敏度: 中</div><div></div></div></div><div>靈敏度：</div><div>設定偵測靈敏度，從 1 到 10。</div><div>區域設定：</div><div>使用電腦滑鼠設定移動偵測區域。粉紅色格子代表未被偵測的區域，而透明的格子代表有偵測的區域。您可以設定多個偵測區域。</div><div>按 [全部清除] 清除先前選擇的偵測區域，變成全部不偵測。</div><div>按 [全部選擇] 選取全區域進行偵測。</div></div>
警報持續時間	設定觸發時的錄影時間 (5 / 10 / 20 / 40 秒)。

◆ 動作

設定攝影機在發生事件時傳送通知給您的方式。

項目	說明
E-Mail	先選取要收到 E-Mail 通知的事件類型。 接著，按 [E-Mail] 字樣設定媒體類型 (H.264 / JPEG / MPEG4)，檔案格式 (AVC / AVI) 及事件錄影時間 (1 到 5 秒)。 當發生選取事件時，攝影機就會將錄好的影片傳送給在 [網路設定] → [郵件管理] 內指定的收件人。
FTP	先選取要收到 FTP 通知的事件類型。 接著，按 [FTP] 字樣設定媒體類型 (H.264 / JPEG / MPEG4)，檔案格式 (AVC / AVI) 及事件錄影時間 (1 到 5 秒)。 當發生選取事件時，攝影機就會將錄好的影片上傳到在 [網路設定] → [影像上傳] 內指定的位置。
簡訊通知	選取要啟動簡訊通知的事件類型。當發生選取事件時，攝影機就會傳送簡訊到您在 [網路設定] → [簡訊通知] 內所設定的電話號碼。
警報發出	先選取要觸發警報裝置的事件類型。 接著，按 [警報發出] 字樣設定觸發規則。(低 / 高)
錄影	選取要啟動事件錄影的事件類型。

3.7 常用設定

3.7.1 常用設定

在 [常用設定] 裡，您可以選擇介面語言並查看攝影機的 MAC 位址。

若要在閒置一段時間後鎖住攝影機登入，請在 [自動鎖定時間] 選擇 [5 分鐘]、[15 分鐘] 或 [30 分鐘]，或選擇 [從不鎖定] 關閉此功能。

註：要從攝影機鎖定的狀態下回復，請輸入登入時使用的密碼。



3.7.2 時間設定

設定日光節約時間和目前的時間，然後按 [儲存] 確認。

時間設定

OSD: ☐ 開啟 ☒ 關閉

日期: 2011/12/09

時間: 23 : 22 : 44

儲存設定

重新載入

日光節約時間

日光節約時間設定

日光節約時間: ☐ 開啟 ☒ 關閉

開始時間: 八月 第一週 星期一 6 : 0 (HH:MM)

結束時間: 十月 第五週 星期一 10 : 0 (HH:MM)

調整時間: 1 : 0 (HH:MM)

儲存設定

重新載入

功能	說明
■ 時間設定	
日期	設定今天的日期。
時間	設定現在的時間。
■ 日光節約時間設定	
日光節約時間	選擇是否要使用日光節約功能（開啟 / 關閉）。
	若啟動了此功能，請設定 [開始時間] 和 [結束時間]，並調整日光節約時間，以小時為單位。

3.7.3 系統日誌

若要依事件類型來快速搜尋想要的系統日誌，按 [上一頁] 或 [下一頁]，或者勾選想要搜尋的事件類型，然後按 [重新查詢]。

若要清除所有系統日誌，請按 [清除全部日誌]。

系統日誌清單

編號	事件	時間	結果
1	遠端登入	2011/12/09 23:14:49	admin
2	遠端登入	2011/12/09 23:14:02	admin
3	遠端登入	2011/12/09 23:01:07	admin
4	遠端登入	2011/12/09 22:55:31	admin
5	遠端登入	2011/12/09 22:33:25	admin
6	遠端登入	2011/12/09 22:27:37	guest
7	遠端登入	2011/12/09 21:34:55	guest
8	遠端登入	2011/12/09 21:29:16	guest
9	遠端登入	2011/12/09 21:23:52	guest
10	遠端登入	2011/12/09 21:14:09	guest
11	遠端登入	2011/12/09 21:05:47	guest
12	遠端登入	2011/12/09 20:55:36	guest
13	遠端登入	2011/12/09 20:47:26	guest
14	遠端登入	2011/12/09 20:41:30	guest
15	遠端登入	2011/12/09 20:36:21	guest
16	遠端登入	2011/12/09 20:19:32	guest

← 上一頁

→ 下一頁

重新查詢

清除全部日誌

3.7.4 連線使用者

您可以查看目前連線到此攝影機的使用者與其連線資訊。若要重新整理清單，請按 [重新查詢]。

- 若要允許匿名登入，請在 [影像匿名登入] 選擇 [開啟]。
- 若不要在登入時輸入影像驗證碼，請在 [Login with CAPTCHA Image] 選擇 [否]。

連線使用者設定

影像匿名登入：☐ 關閉☒ 開啟

登入驗證碼：☐ 是☒ 否

最大上線人數：

帳號	IP位址	權限	媒體類型
admin	61.63.7.65	系統管理者	H264
admin	61.63.7.65	系統管理者	H264

重新查詢

儲存設定重新載入

3.7.5 權限管理

您可以新增擁有不同使用者權限的帳號，或者刪除或修改現有帳號設定。

如何新增帳號

步驟 1：按 [New] (新增)，然後輸入以下欄位。

權限管理

帳號

權限

登入時間

admin

guest

新增權限相關資訊

帳號：

密碼：

確認密碼：

權限：

登入時間：

儲存設定

關閉

新增

修改

刪除

欄位	說明
帳號	設定要用來登入攝影機的帳號。帳號最多只允許 16 個由字母和數字組成的字元。
密碼	設定要用來進行遠端登入的密碼。密碼最多只允許 16 個由字母和數字組成的字元。
確認密碼	再輸入一次密碼確認。
權限	設定帳號的安全權限，以允許控制不同的功能。使用者權限共有四種：「系統使用者」、「超級使用者」、「一般使用者」和「訪客」。
登入時間	選擇此帳號可停留線上的時間：1 分鐘 / 5 分鐘) / 10 分鐘) / 1 小時) / 1 天) / 永久

步驟 2：接著，按一下 [儲存設定] 來儲存與完成帳號的建立。

如何修改或刪除現有帳號

步驟 1：選取想要修改或刪除的帳號。

步驟 2：若要修改帳號，請選擇 [修改] 變更設定，然後再按 [儲存設定]。若要刪除帳號，請按 [刪除]。

註：若帳號清單中只有一個帳號，則無法刪除該帳號。

3.7.6 Google 地圖

此功能用於查看目前攝影機所在位置。

如登入失敗，系統會要求您申請一組 **Google** 地圖金鑰，請依下方指示：

步驟 1：點選 [申請 **Google** 地圖金鑰]，進入申請頁面。。

步驟 2：確認申請條款及細則並輸入網路攝影機之 IP 位址，然後按下 [產生 **API** 金鑰] 按鈕。

步驟 3：複製 **API** 金鑰並回到系統瀏覽頁面中按下 [修改 **Google** 地圖金鑰] 按鈕並貼上內容。




3.7.7 系統維護

韌體更新

此功能可用來升級與更新攝影機功能。

註：在使用此功能之外，請確認已從安裝商或經銷商處取得升級檔案。

註：更新韌體將自動移除原先儲存於攝影機的事件影片。欲進行更新韌體前，請確認重要影像已經備份到您的電腦。

步驟 1：按 [] 搜尋儲存更新檔的位置，然後選擇其中一個。(至多可選四個)



步驟 2：按 [開始更新] 即可開始系統升級。

註：建議保留目前的設定，否則更新後，所有設定都將回復到預設值

註：升級需要一些時間，請勿在這期間中斷電源，否則升級可能會失敗。升級完成後，攝影機將重新啟動。

系統組態備份

此功能是用將您的系統設定複製到 **System.bin** 的檔案裡。

您可以匯入相同的系統設定到另一台攝影機 (舉例：AVN801)，當 AVN801 重新被設為預設值時，您將可以選擇

恢復爲您原先的系統設定值。

在【韌體更新】選項裡，選擇 **System.bin** 檔案，並點選【開始備份】以匯入系統設定。

系統組態備份

在更新韌體版本之前，若您要備份系統組態，請按「開始備份」以進行備份。




系統重新開機

若您需要重新啓動您的系統，請按下【重新開機】以進行系統重新啓動。

系統重新開機

若您要重新啓動您的系統，請按下「重新開機」，以進行系統重新啓動。




播放器下載

若您要播放下載之影像，請先下載並安裝播放器。

選擇【免費下載】以進行播放器下載，點選兩下即開始安裝。

播放器下載

若您要播放下載之影像，請先下載並安裝播放器。



附錄 1 產品規格

■ 網路		
網路壓縮格式	H.264 / MPEG4 / MJPEG	
多重影像傳輸 (Encode 模式、IPS、解析度)	3 (H.264, MJPEG, MPEG4)	
LAN 埠	支援	
LAN 速度	10/100 Based-T Ethernet	
支援的協定	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP,IPv4, Bonjour, UPnP, DNS,UDP,IGMP	
Frame 速率	NTSC:30, PAL:25	
線上使用者人數	10	
安全性設定	1. 多種使用者存取權限與密碼設定 2. 過濾 IP 位址 3. 摘要鑑別	
遠端監控	1. 在 Windows 作業系統使用 Internet Explorer 2. iPhone、iPad 和 Android 行動裝置使用 EagleEyes 監控軟體	
ONVIF 相容性	支援	
■ 攝影機		
影像感測器	1/4" SONY 影像感測器	
影像解析度	SXGA / HD720P / VGA / QVGA	
最低照度	0.1 Lux / F1.5, 0 Lux (紅外線 LED 開啓)	
信噪比	超過 48dB (AGC 關閉)	
鏡頭	f3.8mm / F1.5	
視角	62.7°	
紅外線 LED	35 顆	
紅外線有效範圍	最遠可達 20(米)	
紅外線切換	是	
白平衡	ATW	
AGC	Auto	
IRIS 模式	AES	
外接警報 I/O 埠	是	
POE	是 (IEEE 802.3af)	
麥克風	是	
喇叭	是	
IP 係數	IP67	
電源 (±10%)	12V / 1A	
操作溫度	-20℃~40℃	
尺寸 (mm)**	75(φ) x 114(H)	
■ 其他		
行動監控	iPad, iPhone & Android	
RTC (網路對時)	是	
移動偵測	是	
數位 PTZ	是	否
事件通知方式	影像上傳 / 郵件傳送 / 簡訊通知	
網路瀏覽最低設備需求	• Pentium 4 CPU 1.3 GHz 或更高等級，或同級 AMD • 256 MB RAM • AGP 圖形顯示卡、Direct Draw、32MB RAM • Windows 7、Vista & XP，DirectX 9.0 或更新版本 • Internet Explorer 7.x 或更新版本	

* 規格變動以實際產品為準，將不另行通知。

** 尺寸誤差範圍：± 5mm


附錄 2 傳輸速度參照表

以下資料僅供參考用。

下表所列的傳輸速度會因您實際選取的影像大小、影像品質和影像張數，以及監控畫面複雜度和物體移動頻繁度而有所差異。

測試環境

- 地點：辦公室入口
- 網路傳輸格式：H.264
- 攝影機類型：百萬畫素網路攝影機



靜態畫面：無人出入



動態畫面：僅有一、兩人出入 (不頻繁)


影像規格	影像品質	Frame 速率	(動態畫面) kbps	(靜態畫面) kbps
SXGA	最好	FULL	3253	3216
	高		2375	2160
	一般		1571	1266
	基本		1465	873
VGA	最好		2010	1261
	高		1042	1034
	一般		685	572
	基本		457	350
QVGA	最好		646	366
	高		482	350
	一般		302	286
	基本		168	161
SXGA	最好	1/4	1163	1076
	高		989	715
	一般		855	534
	基本		719	443
VGA	最好		789	571
	高		451	447
	一般		349	237
	基本		217	165
QVGA	最好		269	147
	高		182	131
	一般		164	113
	基本		97	71

影像規格	影像品質	Frame 速率	(動態畫面) kbps	(靜態畫面) kbps
SXGA	最好	1/15	581	374
	高		405	342
	一般		487	248
	基本		337	141
VGA	最好		358	79
	高		201	63
	一般		180	28
	基本		92	15
QVGA	最好		111	84
	高		99	68
	一般		97	54
	基本		58	42


附錄 3 連接 POE 功能

此裝置支援符合 IEEE802.3af 標準規範的 Power-over-Ethernet (POE) 功能。透過同一條網路線，即可傳送電源，不需再另外接電源線，下圖所示為兩種不同 POE 使用狀況，提供參考：

- 若您的 router 或 hub 支援 POE 功能



- 若您的 router 或 hub 不支援 POE 功能 (須加裝 POE 接頭)




附錄 4 如何申請簡訊通知功能的應用程式介面識別碼

欲開啓攝影機的簡訊通知功能，在一事件發生的當下自動發送簡訊到手機，您必須先向 Clickatell 行動簡訊公司，申請應用程式介面識別碼。

註：簡訊通知功能並非免費提供，簡訊通知功能的費用自第十一封簡訊起算。

請依下列指示完成申請步驟。

步驟 1: 登入網頁 <http://www.clickatell.com/login.php>，在 New Customers 頁面裡的下拉式選單，點選 [Clickatell Central (API)]。



步驟 2：填入您的資料以建立一個新帳號，再點選 [CONTINUE]。

註：請記下使用者名稱、密碼和您所指定的行動電話號碼，之後用來接收簡訊通知。

Step 1 of 4 - Select Product


Select one of the products below which you would like to register for:

☒ Clickatell Central ☐ Communicator

Step 2 of 4 - Account Setup

Select a country specific or International account type, based on your requirements for SMS traffic delivery destinations.

International Coverage Account: ☒ INTERNATIONAL ☐ Local Coverage Account: ☐ USA ☐ UK ☐ SA ☐ IN ☐ IE

* Create Username: Security Code: 

* Create Password: *Enter Security Code:

Step 3 of 4 - Personal Information

*First Name: *Country:

*Last Name: *Mobile Number:

* Email Address: (e.g. sample@domain.com)

Personal Use Only ☐

* Company: Job Description:

Company Size: Industry:

Subindustry:

Emails sent to me must be in ☒ Text format or ☐ HTML format

☐ Please send me a weekly update of my account balance via email newsletter

☒ * I accept Clickatell's [Terms and Conditions](#)

步驟 3：當帳號建立成功，系統會自動發信到您所指定的電子信箱，並要求您開通該帳號。點選信件中的連結進入如下圖所示的登入頁面，輸入密碼之後，點選 [Login] 以完成開通帳號的手續。

My Account Login

Customer Login

Existing Clickatell account holders can select their product and login below. Note, username & password are CASE sensitive.

Select Product:

Clickatell Central (API)

Username:

tech

ClientID:

CTHD43

Password:

Login

Enter the password you set to log in.

步驟 4：輸入您欲接收簡訊通知的行動電話號碼（包含國碼），然後點選 [SEND ACTIVATION CODE]。系統會傳送開通帳號的驗證碼到您輸入的號碼，請確認是否接收到 Clickatell 傳來的簡訊通知。

Verify your Mobile Number

For security reasons you are required to verify your mobile number before you can receive non-test SMS messages.

Your activation code will be sent to:

886912666475

SEND ACTIVATION CODE

If this is not your number, please retype your mobile number in the box above and click the "Send Activation Code" button.

Enter your activation code here:

VERIFY NOW

步驟 5：返回 Clickatell 頁面，點選 [Manage my Products] 的按鈕。然後，在從 [My Connections]的下拉式選單裡，點選 [HTTP]。

Central HomeMy SettingsManage my ProductsBillingMessage ReportsHelp

Manage my Products

My Connections

Converters

Two-Way Messaging

Application Forms

Two-Way Application

SA Shortcode MO

Namibia Shortcode

USA Shortcode

UK Shortcode

Canada Shortcode

Clickatell ICM

Test Message in Message Box

Please Note that Clickatell pre-populates all test credits with a standard test message. Once you have purchased Clickatell credits, the test message will be removed and you will be able to send personalized text messages.

Buy SMS Credits

My Connections:

My Connections

Add Connection

Add Connection

HTTP

SMTP

FTP

XML

COM

SMPP

SOAP

Select "HTTP".

步驟 6：在 In [Add HTTP API] 頁面輸入使用者名稱，確認 dial prefix 是否正確且 callback type 為 [HTTP GET]，確認無誤後，點選 [Submit]。

Add HTTP API - Bold Items Required

Name:

IP_MSG

IP Lock Down:

Dial Prefix:

Taiwan (886)

Callback Type:

HTTP GET

Callback Url:

Callback Username:

Callback Password:

Submit

Minimum information required

步驟 7：取得應用程式介面識別碼，如下圖所示。

註：請記下應用程式介面識別碼，後續設定簡訊通知功能時會用到。

My Connections:

Add Connection


Show All Connection Types

Name	Type	API ID	Dialing Code
IP_SMS	SMTP API	3218637	886 Taiwan
IP_MSG	HTTP	3220810	886 Taiwan

1 to 2 of 2

附錄 5 常見問題集

如有更多關於 EagleEyes 的問題，請上官網 www.eagleeyesccctv.com/supp_QnA.aspx。

問題	解答
當我在家中或是辦公室時，我可以成功連上攝影機，即使是沒有無線網路的情況下。但是一旦離開家裡或是辦公室，我卻無法從手機（連上 3G 網路）或是桌電（連上網路）進入攝影機，為什麼？	您尚未成功連上網際網路，您連上的網路為區域網路。所以，請依說明書的指示完成網路設定，說明書下載請至下方連結： www.surveillance-download.com/user/m357a.swf ；或是建議您與當地安裝商或當地供應商聯繫，協助安裝事宜。因為網路設定對於初次設定的人而言，難度較高。
影像看起來很不流暢。為什麼？	影像的流暢度會受到區域網路上傳頻寬、Router 的硬體效能、攝影機下載頻寬和畫面複雜度等因素有關。 ^L (建議設定) 如需看到非常流暢的影像，解析度請選取 [QVGA]；如需看到最好的畫質呈現，解析度請選取 [SXVGA] 或 [HD1080P]；如對影像流暢度和畫面沒有特殊要求，建議解析度則選取 [VGA]。
即時的影像畫面一直閃爍。為什麼？	您必須調整攝影機的電源頻率切換至 [60 Hz] 或 [50 Hz]。 iPhone 使用者，進入攝影機畫面，選擇即時畫面右上角的  進入 IPCAM 設定頁面，然後選擇 [進階設定] → [攝影機]，以變更設定。 Internet Explorer 瀏覽器使用者，登入攝影機後選擇 [系統設定] → [攝影機設定] → [攝影機設定]。

附錄 6 錄影時間表

下表列出在各個錄影解析度下能錄製的總預計時間。

每種解析度測出的錄影時間，是在以下兩種警報觸發情況時所得出的平均值，僅供參考。

錄影時間會因您選擇的錄影解析度、影像品質和影錄張數、監視畫面複雜度，以及監視畫面出現移動物體的頻繁度，而有所不同。

測試環境

- 地點：辦公室
- 監控區域：離攝影機 1.5 公尺遠的位置
- 警報觸發情境：
 - (1) 一個人經過監控區域，然後馬上離開。
 - (2) 兩個人經過監控區域，一個人馬上離開，另一個人停留一會兒才離開。

錄影解析度	SXGA	VGA	QVGA
錄影時間 (秒)	25	115	211