## **Product Information Sheet**

trol gear, light-

control

ing

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| sources  | LLEGATED REGOT   | -A11014 (L0) 2013/2     | olo with regard to energ   | gy labelling of light |  |  |
|--|------------------|-------------------------|--|-----------------------|--|--|
| Supplier's name  | e or trade mark: | Velleman                |  |                       |  |  |
| Supplier's address: public info, Legen Heirweg 33, 9890 Gavere, BE   |                  |                         |  |                       |  |  |
| Model identifie  | r: LS12M230WW    | /1                      |  |                       |  |  |
| Type of light so   | urce:            |                         |  |                       |  |  |
| Lighting technology used:  |                  | LED                     | Non-directional or directional:  | NDLS                  |  |  |
| Light source cap-type  |                  | NA                      |  |                       |  |  |
| (or other electric interface)  |                  |                         |  |                       |  |  |
| Mains or non-mains:  |                  | NMLS                    | Connected light source (CLS):  | No                    |  |  |
| Colour-tuneable light source:  |                  | No                      | Envelope:  | -                     |  |  |
| High luminance light source:   |                  | No                      |  |                       |  |  |
| Anti-glare shield:   |                  | No                      | Dimmable:  | No                    |  |  |
|  |                  | Product para            |  |                       |  |  |
| Parameter  |                  | Value                   | Parameter  | Value                 |  |  |
|  |                  | General product p       | parameters:  |                       |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                  | 7                       | Energy efficiency class  | F                     |  |  |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                  | 709 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 500                 |  |  |
| On-mode power (P <sub>on</sub> ), ex-<br>pressed in W  |                  | 7,2                     | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00                  |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                  | -                       | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 85                    |  |  |
| Outer dimensions without   | Height           | 3                       | Spectral power dis-  | See image             |  |  |
|  | Width            | 10                      | tribution in the   | in last page          |  |  |
| separate control gear, light-  | Depth            | 500                     | range 250 nm to 800<br>nm, at full-load  |                       |  |  |

nm, at full-load

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |      |                              |       |  |  |  |  |
|--|------|------------------------------|-------|--|--|--|--|
| Claim of equivalent power <sup>(a)</sup>                                   | -    | If yes, equivalent power (W) | -     |  |  |  |  |
|  |      | Chromaticity coordi-         | 0,422 |  |  |  |  |
|  |      | nates (x and y)              | 0,401 |  |  |  |  |
| Parameters for LED and OLED light sources:                                 |      |                              |       |  |  |  |  |
| R9 colour rendering index value  | 39   | Survival factor              | 1,00  |  |  |  |  |
| the lumen maintenance factor   | 0,99 |                              |       |  |  |  |  |

(a)'-': not applicable; (b)'-': not applicable;

